

**Federal Aviation
Administration**

Transmittal Letter 20-09

February 24, 2020

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
4/23/2020	AZ	PHOENIX	PHOENIX SKY HARBOR INTL	0/7654	2/24/2020	RNAV (GPS) Y RWY 7R AMDT 1A

AIRAC Date: 23 APRIL 2020

FDC **0/7654** PHX IAP PHOENIX SKY HARBOR INTL, PHOENIX, AZ. RNAV (GPS) Y RWY 7R, AMDT 1A... CHART CIRCLING ICON. LNAV CAT C VIS 1 SM. CIRCLING CAT C MDA 2040/HAA 905 VIS 2 3/4, CAT D MDA 2560/HAA 1425 VIS 3. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT C 1000-2 3/4, CAT D 1500-3. CHANGE NOTE TO READ: FOR INOPERATIVE ALS, INCREASE VISIBILITY LPV ALL CATS TO 7/8 SM, LNAV/VNAV ALL CATS TO 1 1/8 SM, LNAV CATS A/B TO 1 SM AND C/D TO 1 3/8 SM. CHANGE NOTE TO READ: RWY 7R HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. THIS IS RNAV (GPS) Y RWY 7R, AMDT 1B. 2002211826-PERM