

**Federal Aviation  
Administration**

**Transmittal Letter 22-22**

**September 2, 2022**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10/6/2022	MS	Starkville	George M Bryan	2/6467	8/15/2022	RNAV (GPS) RWY 18, Amdt 2B

**AIRAC Date: 6 OCTOBER 2022**

FDC 2/6467 STF IAP GEORGE M BRYAN, STARKVILLE, MS. RNAV (GPS) RWY 18, AMDT 2B... DELETE PBN REQUIREMENTS NOTE: RNP APCH. PBN REQUIREMENTS NOTE: RNP APCH-GPS. ALTERNATE MINMUMS: CAT D, 800-2 1/4; NA WHEN LOCAL WEATHER NOT AVAILABLE. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GOLDEN TRIANGLE RGNL ALTIMETER SETTING AND INCREASE ALL DA/MDA 40 FEET; INCREASE LPV ALL CATS, LNAV/VNAV ALL CATS AND LNAV CATS C/D VISIBILITY 1/8 MILE, INCREASE CIRCLING CAT C VISIBILITY 1/4 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GOLDEN TRIANGLE RGNL ALTIMETER SETTING AND INCREASE LPV DA TO 673 FEET, INCREASE LNAV/VNAV DA TO 656 FEET AND VISIBILITIES ALL CATS 1/8 SM. INCREASE ALL MDAS 40 FEET AND LNAV VISIBILITY CAT C/D 1/8 SM, AND CIRCLING VISIBILITY CAT C 1/4 SM.. THIS IS RNAV (GPS) RWY 18, AMDT 2C. 2208091444-PERM