

**Federal Aviation
Administration**

Transmittal Letter 22-03

December 10, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
1/27/2022	TX	Victoria	Victoria Rgnl	1/5743	9/24/2021	RNAV (GPS) RWY 13, Orig

AIRAC Date: 27 JANUARY 2022

FDC 1/5743 VCT IAP VICTORIA RGNL, VICTORIA, TX. RNAV (GPS) RWY 13, ORIG... DELETE NOTE: BARO-VNAV NA WHEN USING PORT LAVACA ALTIMETER SETTING. DELETE NOTE: VDP NA WHEN USING PORT LAVACA ALTIMETER SETTING. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PORT LAVACA ALTIMETER SETTING AND INCREASE LPV DA TO 367 FEET AND LNAV/VNAV DA TO 417 FEET; INCREASE ALL MDAS 60 FEET AND VISIBILITY CAT C AND D 1/4 SM, CAT E 1/8 SM. DELETE NOTE: FOR INOPERATIVE ALS WHEN USING PORT LAVACA ALTIMETER SETTING, INCREASE LPV CAT E VISIBILITY TO 3/4 SM, LNAV/VNAV ALL CATS VISIBILITY TO 7/8 SM, AND LNAV CAT E VISIBILITY TO 1 1/8 SM. THIS IS RNAV (GPS) RWY 13, ORIG-A. 2109101400-PERM