

**Federal Aviation
Administration**

Transmittal Letter 23-16

June 9, 2023

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/13/2023	MO	Lee'S Summit	Lee'S Summit Muni	3/1626	5/25/2023	RNAV (GPS) RWY 29, Amdt 3

AIRAC Date: 13 JULY 2023

FDC 3/1626 LXT IAP LEE'S SUMMIT MUNI, LEE'S SUMMIT, MO. RNAV (GPS) RWY 29, AMDT 3... CHANGE NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 54C. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE PROFILE NOTE: *LNAV ONLY. DELETE ASTERISK FROM VDP 1 NM TO RW29. DELETE ASTERISK AT MINIMUM ALTITUDE 1580 AT ZEVED. DELETE NOTE: DME/DME RNP-0.3 NA. LPV VISIBILITY 1 SM ALL CATS. LNAV/VNAV VISIBILITY 1 SM ALL CATS. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHARLES B. WHEELER DOWNTOWN ALTIMETER SETTING: INCREASE LPV DA TO 1322 FEET; INCREASE LNAV/VNAV DA TO 1359 FEET; INCREASE ALL MDA 80 FEET AND VISIBILITY CATS C AND D 1/4 SM.. THIS IS RNAV (GPS) RWY 29, AMDT 3A. 2305241816-PERM