

**Federal Aviation  
Administration**

**Transmittal Letter 23-01**

**November 11, 2022**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
12/29/2022	VT	Morrisville	Morrisville-Stowe State	2/6396	10/24/2022	RNAV (GPS) Z RWY 19, Amdt 2

**AIRAC Date: 29 DECEMBER 2022**

FDC 2/6396 MVL IAP MORRISVILLE-STOWE STATE, MORRISVILLE, VT. RNAV (GPS) Z RWY 19, AMDT 2... VISIBILITY LPV 1 1/2 ALL CATS, LNAV/VNAV 2 1/2 ALL CATS. DELETE CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -28C (-18F) OR ABOVE 54C (130F). CHART NOTE: BARO-VNAV NA. CHANGE CHART NOTE TO READ: VDP NA WHEN USING BURLINGTON ALTIMETER SETTING. CHANGE CHART NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BURLINGTON ALTIMETER SETTING: INCREASE LPV DA TO 1380 FEET AND ALL VISIBILITIES 3/8 SM. INCREASE LNAV/VNAV DA TO 1690 FEET AND ALL VISIBILITIES 1/2 SM. INCREASE ALL MDAS 120 FEET. ALTERNATE MINIMUMS: CAT A/B 1100-2 1/2, CAT C 1300-3; NA WHEN LOCAL WEATHER NOT AVAILABLE. DELETE CHART NOTE: DME/DME RNP-0.3 NA. ADD PBN REQUIREMENTS NOTE: RNP APCH - GPS. THIS IS RNAV (GPS) Z RWY 19, AMDT 2A. 2210191724-PERM