

U.S. DEPARTMENT of TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

DEPARTURE PROCEDURES / TAKEOFF MINIMUMS

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

COORDINATED

ATA
☐

AAT
☐

ALPA
☐

APA
☐

AOPA
☒

NBAA
☒

OTHER (specify)
☒

ZAU, AIRPORT MANAGER

TAKEOFF MINIMUMS:

RWY 13, 31 STANDARD.

IFR DEPARTURE PROCEDURE:

RWY 31: CLIMB RUNWAY HEADING TO 1800 BEFORE TURNING NORTH.

TAKEOFF OBSTACLES:

DEPARTURE OBSTACLES:

RWY 31: 1550 TOWER (50-0638) 440601 / 891824

DEVELOPED BY		APPROVED BY	
SIGNATURE: <i>John R. Pannell</i> JOHN R. PANNELL (STEVEN A. VARGAS)	DATE: 05/12/98 FIFO: AVN-140	SIGNATURE: <i>Joseph E. Rooney</i> JOSEPH E. ROONEY	DATE: MAY 14 1998 FIFO: AVN-140
CITY AND STATE WAUTOMA, WI	AIRPORT WAUTOMA MUNICIPAL	EFFECTIVE ROUTINE	AMDT. NO. ORIGINAL