U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
LAL VORTAC (IAF)	LINTY/LAL 7.00 DME	103.71 / 7.00	2000
LINTY/LAL 7.00 DME (IF)	MONAY/LAL 17.00 DME	103.71 / 10.00 (LAL R-104)	1600

MISSED APPROACH

MAP: MADCY/LAL 21.42 DME FIX

CLIMB TO 700 THEN CLIMBING RIGHT TURN TO 1600 ON LAL VORTAC R-104 TO MONAY/LAL 17.00 DME AND HOLD.

ADDITIONAL FLIGHT DATA:

HOLD W, RT, 103.71 INBOUND.
FAS OBST: 360 AAO 275253N/0814216W

1. PT ____ SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. HOLD W LAL VORTAC, RT, 103.71 INBOUND, 2000 FT. IN LIEU OF PT (IAF)
3. FAC 103.71 FAF MONAY/LAL 17.00 DME DIST FAF TO MAP ____ THLD ____
4. MIN. ALT LAL VORTAC 2000, LINTY 2000, MONAY 1600
8. MSA FROM: LAL VORTAC 2700

MAG VAR: 1E EPOCH YEAR:1965

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A X

CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
CIRCLING	620	1	493	620	1 1/4	493	620	1 1/2	493	680	2	553			

NOTES:

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BARTOW ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET.
CHART NOTE: PROCEDURE NA AT NIGHT.

QUALITY 1 CHECKED

CITY AND STATE	ELEVATION: 127 TDZE: AIRPORT NAME:	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP VOR/DME OR GPS-B
LAKE WALES, FL	LAKE WALES MUNI	LAL	VOR/DME-B, AMDT 3 25 AUG 2011	AMDT 2 DATE 10/27/2005

FAA FORM 8260-5 / April 2006 (computer generated)