

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
 LOC STANDARD INSTRUMENT APPROACH PROCEDURE
 FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: 6.28 MILES AFTER NALLS INT	
SANTY INT/ 29.49 DME	NALLS INT/SNS VORTAC 16.50 DME/RADAR	113.00 / 12.99 (SNS R-293)	4000	CLIMBING RIGHT TURN TO 5000 DIRECT SNS VORTAC AND HOLD, CONTINUE CLIMB-IN-HOLD TO 5000.	
SNS VORTAC	NALLS INT/SNS VORTAC 16.50 DME/RADAR	293.00 / 16.50	4000		
				ADDITIONAL FLIGHT DATA: HOLD NW, LT, 113.00 INBOUND. CHART FAS OBST: 419 TREE 365420N/1214917W NALLS INT TO RW02: 3.02/48. CHART IN PLANVIEW: (CFBRS) 364520.71N-1215554.93W	

1. PT R SIDE OF COURSE 198.31 OUTBOUND 3000 FT WITHIN 10 MILES OF NALLS (IAF)
 2. _____
 3. FAC 018.31 FAF NALLS INT DIST FAF TO MAP 6.28 THLD 6.28
 4. MIN. ALT NALLS 2200
 8. MSA FROM: SNS VORTAC 100-220 6300, 220-310 4200, 310-100 5200

MAG VAR: 14E

EPOCH YEAR: 2015

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD						
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-2	700	1	561	700	1	561	700	1 5/8	561	700	1 5/8	561			
CIRCLING	700	1	537	700	1	537	700	1 5/8	537	720	2	557			

NOTES:

CHART NOTE: CIRCLING NA AT NIGHT.
 CHART NOTE: WHEN VGSI INOP, PROCEDURE NA AT NIGHT.
 CHART NOTE: CIRCLING NA WEST OF RWY 02-20.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MONTEREY ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET AND VISIBILITY CATS C AND D 1/8 MILE AND CIRCLING CAT C 1/8 MILE.

QUALITY
CHECKED

CITY AND STATE WATSONVILLE, CA	ELEVATION: 163 THRE: 139 AIRPORT NAME: WATSONVILLE MUNI	FACILITY IDENTIFIER: I-AYN	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: LOC RWY 2, AMDT 4 7 MARCH 2013	SUP
				AMDT 3
				DATE 01/15/2009

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

LOC STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.



CITY AND STATE

WATSONVILLE, CA

ELEVATION: 163

THRE: 139

AIRPORT NAME:

WATSONVILLE MUNI

FACILITY
IDENTIFIER:

I-AYN

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

LOC RWY 2, AMDT 4

7 MARCH 2013

SUP:

AMDT: 3

DATED: 01/15/2009

FLIGHT STANDARDS SERVICES - FAR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KWVIK2FL02	ASANTY	010SANTYK2EA0E	IF						18000		0	NS
SUSAP	KWVIK2FL02	ASANTY	020NALLSK2EA0E	TF					+ 04000			0	NS
SUSAP	KWVIK2FL02	ASANTY	030NALLSK2EA0EE AL	PI	IAYNK2	1984007124330100PI			+ 03000			0	NS
SUSAP	KWVIK2FL02	ASNS	010SNS K2D OV	IF						18000		0	NS
SUSAP	KWVIK2FL02	ASNS	020NALLSK2EA0E	TF					+ 04000			0	NS
SUSAP	KWVIK2FL02	ASNS	030NALLSK2EA0EE AL	PI	IAYNK2	1984007124330100PI			+ 03000			0	NS
SUSAP	KWVIK2FL02	L	010CFBRSK2EA0E I	IF	IAYNK2	19830131	PI		+ 03000	18000		0	NS
SUSAP	KWVIK2FL02	L	020NALLSK2EA0E F	CF	IAYNK2	1984007101800060PI			+ 02200		SNS BK2D	0	NS
SUSAP	KWVIK2FL02	L	030RW02 K2PG0GY M	CF	IAYNK2	1983000801800063PI			00187	-302		0	NS
SUSAP	KWVIK2FL02	L	040 0 M	CA		0183			+ 00563			0	NS
SUSAP	KWVIK2FL02	L	050SNS K2D OVY R	DF					+ 05000			0	NS
SUSAP	KWVIK2FL02	L	060SNS K2D OVE L	HM		1130T010			+ 05000			0	NS

[illegible][illegible]

3 MAY 11
CHECKED

CITY AND STATE WATSONVILLE, CA	ELEVATION: 163	TDZE: 139	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: WATSONVILLE MUNI		I-AYN	LOC RWY 2, AMDT 4	AMDT: 3
				7 MARCH 2013	DATED: 01/15/2009

FLIGHT STANDARDS SERVICES - FAR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

MSA

123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAP KWVIK2SSNS K2D B

0 040130044251302800522528004006325

M

QUALITY
1
CHECK

FACILITY
IDENTIFIER:
I-AYN

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
LOC RWY 2, AMDT 4
7 MARCH 2013

SUP:	
AMDT:	3
DATED:	01/15/2009

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

LOC STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES - FAR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - LOC

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	PO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	SANTY	SANTY	010		IF		FB					
	SANTY	NALLS	020		TF		FB				AA 04000	
	SANTY	NALLS	030	IAF	PI	L	FB		243.3 ()	010.0	AA 03000	
	SNS	SNS	010		IF		FB					
	SNS	NALLS	020		TF		FB				AA 04000	
	SNS	NALLS	030	IAF	PI	L	FB		243.3 ()	010.0	AA 03000	
		CFBRS	010	FACF	IF		FB				AA 03000	
		NALLS	020	PAF	CF		FB		018.0 ()	006.0	AA 02200	
		RW02	030	MAP	CF		FO		018.0 ()	006.3	AT 00187	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	PO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		018.3 ()		AA 00563	
	SNS	050		DF	R	FO				AA 05000	
	SNS	060		HM	L	FO		113.0 ()	T01.0	AA 05000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	SNS	N363949.81	W1213611.47	N3639.830	W12136.191
	CFBRS	N364520.71	W1215554.93	N3645.345	W12155.916
	NALLS	N365025.94	W1215156.34	N3650.432	W12151.939
	SANTY	N365845.26	W1220423.07	N3658.754	W12204.385
	RW02	N365544.53	W1214744.86	N3655.742	W12147.748
	IAYN (LOC)	N365625.51	W1214712.56	N3656.425	W12147.209

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW02	00139	56

QUALITY
1
CHECKED

CITY AND STATE
WATSONVILLE, CA

ELEVATION: 163 TDZE: 139
AIRPORT NAME:
WATSONVILLE MUNI

FACILITY
IDENTIFIER:
I-AYN

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
LOC RWY 2, AMDT 4
7 MARCH 2013

SUP:
AMDT: 3
DATED: 01/15/2009