

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW04 CLIMBING LEFT TURN TO 4000 DIRECT LOPEZ AND HOLD. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 1379 TREE 413447N/0754451W CHART VDP AT 1.12 MILES TO RW04. CEMUS TO RW04: 3.49/40
LVZ VORTAC	LOPEZ (FO)	321.82 / 15.99	5000	
LACIE (IAF)	LOPEZ (NOPT) (FB)	141.53 / 10.44	4000	
SWANK (IAF)	LOPEZ (NOPT) (FB)	058.05 / 12.19	4000	
LOPEZ (IF/IAF)	CEMUS (FB)	070.95 / 5.22	4000	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD W LOPEZ, LT, 070.95 INBOUND, 4000 FT. IN LIEU OF PT (IAF)
- FAC: 050.74 FAF: CEMUS DIST FAF TO MAP: 7.50 THLD: 7.50
- MIN. ALT: LOPEZ 4000, CEMUS 4000, FENUN/2.60 NM TO RW04 2180
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS CLEAR
- MSA FROM: RW04 4000

MAG VAR: 12W

EPOCH YEAR: 1985

MINIMUMS

TAKEOFF: <input type="checkbox"/>	STANDARD <input checked="" type="checkbox"/>	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A <input checked="" type="checkbox"/>												
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1640	1	431	1640	1	431		NA			NA				
CIRCLING	1720	1	511	1720	1	511		NA			NA				

WILKES-BARRE/SCRANTON INTL ALTIMETER SETTING MINIMUMS

LNAV MDA	1720	1	511	1720	1	511		NA			NA				
CIRCLING	1800	1	591	1800	1	591		NA			NA				

NOTES:

CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, USE WILKES-BARRE/SCRANTON INTL ALTIMETER SETTING.

CHART NOTE: VDP NA WHEN USING WILKES-BARRE/SCRANTON INTL ALTIMETER SETTING.

CITY AND STATE FACTORYVILLE, PA	ELEVATION: 1209 TDZE: 1209 AIRPORT NAME: SEAMANS FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, ORIG FEB 14 2008	SUP: AMDT: NONE DATED
------------------------------------	--	---------------------------------	---	-----------------------------

TLDP-04



Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SUP:	
AMDT:	NONE
DATED:	✓

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

SUSAP 9N3 K6GRW04 0025000358 N41350812W075452983+0800 01184000040050

MSA 1 2 3 4 5 6 7 8 9 0 1 2 3
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
SUSAP 9N3 K6SRW04 K6PG 0 25180040 M

CITY AND STATE
FACTORYVILLE, PA

ELEVATION: 1209 TDZE: 1209
AIRPORT NAME:
SEAMANS FIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 4, ORIG
FEB 14 2008

SUP:
AMDT: NONE
DATED:

