

CONTINUED FROM PRECEDING PAGE

RADIO AIDS TO NAVIGATION: NOTAM FILE PVD.

PROVIDENCE (H) (DH) VOR/DME 115.6 PVD Chan 103 N41°43.46' W71°25.78' 164° 13.3 NM to fld. 49/14W.

VOR unusable:

085°-105° byd 12 NM blo 5,500'

085°-105° byd 8 NM blo 3,000'

106°-294° byd 30 NM blo 3,000'

295°-330° byd 30 NM blo 6,000'

331°-084° byd 30 NM blo 3,000'

DME unusable:

085°-105° byd 12 NM blo 5,500'

085°-105° byd 8 NM blo 3,000'

106°-152° byd 11 NM blo 2,000'

106°-152° byd 20 NM blo 4,000'

153°-294° byd 30 NM blo 3,000'

295°-330° byd 30 NM blo 6,000'

331°-084° byd 30 NM blo 3,000'

LOC/DME 108.5 I-OTI Chan 22 Rwy 22. LOC unmonitored.

NORTH CENTRAL STATE (See PAWTUCKET on page 325)

NORTH KINGSTOWN

QUONSET STATE (OQU)(KOQU) P (ARNG ANG) 3 NE UTC-5(-4DT) N41°35.83' W71°24.73'

18 B TPA—See Remarks LRA NOTAM FILE OQU

RWY 16-34: H7504X150 (ASPH-GRVD) D-175, 2S-175 HIRL

RWY 16: MALSR. PAPI(P4L)—GA 3.0° TCH 58'. Trees.

RWY 34: PAPI(P4L)—GA 3.0° TCH 50'. Thld dsplcd 403'.

RWY 05-23: H4000X75 (ASPH) S-12.5 MIRL

RWY 05: REIL. PAPI(P4L)—GA 3.0° TCH 40'. Pole.

RWY 23: REIL. PAPI(P4R)—GA 3.0° TCH 40'.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 16: TORA-7100 TODA-7100 ASDA-7100 LDA-7100

RWY 34: TORA-7500 TODA-7500 ASDA-7500 LDA-7100

SERVICE: FUEL 100LL, JET A LGT ACTVT MALSR Rwy 16; REIL Rwy 05 and 23; PAPI Rwy 05 and 23; MIRL Rwy 05-23, HIRL Rwy 16-34; twy lghts—CTAF. MILITARY—FUEL J8(Mil), A+ (FBO opr 1100-0200Z). PPR mandatory dur non-duty hr. Ctc C401-295-5020 (NC-100LL, A)

AIRPORT REMARKS: Unattended 0300-1200Z± Sat-Sun. Deer, birds and waterfowl on and in/ov arpt. Nmrs cranes on and in/ov arpt. Rwy 23 uneven pavement aprxly 100-400 ft fm AER 23 thr. Ctc amgr 401-295-5020. Rwy 34 uneven pavement aprxly 1,000-2,000 ft fm AER 34 thr. Civil acft use ctn, heightened scity measures in efct on ANG and Army ramps UFN. Rcemd Twy A-2 inbtxn dep for Rwy 34, 5,500 ft rmng. Ctc amgr 401-295-5020. Twy R and Twy E clsd indef. Lgtd cranes 125' high at pier 1000' southeast of Rwy 05. 180° turns for acft over 12,500 lbs GWT prohibited on Rwy 16-34. Rwy conds may not be mnt or rprtd when arpt is unatndd. Ctc RI arpt corporation ops at 401-691-2265. Ldg fee coml and non Rhode Island registered acft/ovngt prkg fee. Flight Notification Service (ADCUS) available.

MILITARY REMARKS: RSTD 180° turns for acft over 12,500 lbs GWT proh on Rwy 16-34. MISC Rwy 16 8000' avbl for mil acft only. TFC PAT TPA—Rotary/Wing 700', Fixed/Wing 1000' AGL. ANG PPR for svcg and use of ANG prkg ramp only. AMOPS ops 1200-2230Z± Tue-Fri, excp holidays, DSN 476-3404/3405, Tsnt acft inbd to ANG prkg ramp ctc Quahog, comd post, 15 min prior to ldg. BASH program in eff. 1 Jul-31 Oct are dsgrnd BASH Phase II periods for migratory bird act. Incrd haz fm Canadian geese flying east to west over rwy. Inbd acft ctc Quahog/Rhody Ops for latest bird watch conds. Tmprry storage of classified mtrls up to secret at comd post. Acft req cust/ag ctc AMOPS 7 days prior to arr. ARNG Opr 1200-2230Z± Tue-Fri, exc hol. PPR for tsnt mil acft ldg, prkg ARNG Ramp and fuel ctc DSN 247-4539, C401-275-4539. Ltd prkg, fuel and maint avbl, prkg Pad 3 clsd UFN. Call Hope Ops 274.30 (PRI), 36.80 (ALTN). PPR to use lcl trg area.

AIRPORT MANAGER: 401-691-2000

WEATHER DATA SOURCES: AWOS-3PT 118.6 (401) 294-2197.

COMMUNICATIONS: CTAF 126.350 ATIS 118.6 (Tue-Fri 1300-0400Z±, Sat 1400-2200Z±, Sun 1500-2300Z±, clsd Mon and hols) UNICOM 122.950

Ⓡ PROVIDENCE APP/DEP CON 123.675 244.875 (Sun-Fri 1030-0530Z±, Sat 1030-0500Z±) other times ctc

BOSTON CENTER APP/DEP CON 124.85 307.9

TOWER 126.35 (Tue-Fri 1300-0400Z±, Sat 1400-2200Z±, Sun 1500-2300Z±, clsd Mon and hols)

CLNC DEL 134.5 ARNG OPS 274.3

CLEARANCE DELIVERY PHONE: For CD when Apch clsd ctc Boston ARTCC at 603-879-6859.

CONTINUED ON NEXT PAGE

RHODE ISLAND

CONTINUED FROM PRECEDING PAGE

AIRSPACE: CLASS D svc 1300-0400Z‡ Tue-Fri, 1400-2200Z‡ Sat, 1500-2300Z‡ Sun, clsd Mon and hol; other times CLASS G.

RADIO AIDS TO NAVIGATION: NOTAM FILE PVD.

PROVIDENCE (H) (DH) VORW/DME 115.6 PVD Chan 103 N41°43.46' W71°25.78' 188° 7.7 NM to fld. 49/14W.

VOR unusable:

- 085°-105° byd 12 NM blo 5,500'
- 085°-105° byd 8 NM blo 3,000'
- 106°-294° byd 30 NM blo 3,000'
- 295°-330° byd 30 NM blo 6,000'
- 331°-084° byd 30 NM blo 3,000'

DME unusable:

- 085°-105° byd 12 NM blo 5,500'
- 085°-105° byd 8 NM blo 3,000'
- 106°-152° byd 11 NM blo 2,000'
- 106°-152° byd 20 NM blo 4,000'
- 153°-294° byd 30 NM blo 3,000'
- 295°-330° byd 30 NM blo 6,000'
- 331°-084° byd 30 NM blo 3,000'

ILS/DME 109.5 I-OQU Chan 32 Rwy 16. Class IT. Preventive maint sched 1400-1600Z‡ Thur. Unmonitored when ATCT clsd.



HELIPAD H1: H45X45 (ASPH)

HELIPAD H2: H45X45 (ASPH)