

RADAR MINS

19171

N1

RADAR INSTRUMENT APPROACH MINIMUMS

FORT SMITH, AR

Amdt 8D, 20JUN19 (19171) (FAA)

ELEV 469

FORT SMITH RGNL (FSM)

RADAR-1 120.9 343.75 **T** **A**

	RWY	GP/TCH/RPI	CAT	DA/	HAT/	CEIL-VIS	CAT	DA/	HAT/	CEIL-VIS
				MDA-VIS	HAA			MDA-VIS	HAA	
ASR	25		AB	1040/24	594	(600-½)	C	1040/50	594	(600-1)
			D	1040/60	594	(600-1¼)	E	1040-1½	594	(600-1½)
	1	AB	1140-1	692	(700-1)	C	1140-2	692	(700-2)	
		D	1140-2¼	692	(700-2¼)	E	1140-2½	692	(700-2½)	
	7	AB	1200-½	731	(800-½)	C	1200-1½	731	(800-1½)	
		D	1200-1¾	731	(800-1¾)	E	1200-2	731	(800-2)	
CIRCLING	ALL RWY	AB	1200-1	731	(800-1)	C	1200-2	731	(800-2)	
		D	1200-2¼	731	(800-2¼)	E	1200-2½	731	(800-2½)	

When control tower closed ASR not authorized.

Rwy 1 helicopter visibility reduction below ¼ SM not authorized.

Rwy 7 helicopter visibility reduction below ¼ SM not authorized.

Circling CAT E NA when R-2401B active.

Circling NA northwest of Rwy 7 and 19 for CAT E.

For inoperative MALSR, increase S-7 CAT E visibility to 2½ miles, and S-25 CAT E visibility to 2 miles.

HENRY POST AAF (KFSI), OK (Fort Sill) (Amdt 13, 19171 USA)

ELEV 1188

RADAR - (E) 120.55 322.4 **T** **A** NA

	RWY	GS/TCH/RPI	CAT	DH/	HAT/	CEIL-VIS
				MDA-VIS	HAA	
ASR	36 ²		AB	1600/40	413	(500-¾)
			CDE	1600/50	413	(500-1)
			AB	1880-1	692	(700-1)
CIR ¹	18-36		CDE	1880-2	692	(700-2)
			AB	1880-1	692	(700-1)
			C	1880-2	692	(700-2)
			D	1920-2¼	732	(800-2¼)
			E	1940-2¾	752	(800-2¾)

When local altimeter setting not received, use Lawton-Ft Sill Rgnl altimeter setting.

¹Circling NA for CAT E W of Rwy 18-36.

²When ALS inop, increase CAT CDE RVR to 60.

10 OCT 2019 to 07 NOV 2019

10 OCT 2019 to 07 NOV 2019

SC-1

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

19171

N1

RADAR MINS

19171

RADAR INSTRUMENT APPROACH MINIMUMS

LAWTON, OK

Amdt 4A, 10JAN00 (00010) (FAA)

ELEV 1110

LAWTON-FORT SILL RGNL (LAW)

RADAR-1 - 120.55 322.4

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	35		ABC	1560-¾	471	(500-¾)	D	1560-1	471	(500-1)
CIRCLING	ALL RWY		AB D	1600-1 1680-2	490 570	(500-1) (600-2)	C	1620-1½	510	(600-1½)

LAWTON, OK

Amdt 1B, 08AUG02 (02220) (FAA)

ELEV 1110

LAWTON-FORT SILL RGNL (LAW)

RADAR-2 - 120.55 322.4


	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VS</u>
ASR	17		AB	1620-1	510	(600-1)	CD	1620-1½	510	(600-1½)
CIRCLING	ALL RWY		AB D	1620-1 1680-2	510 570	(600-1) (600-2)	C	1620-1½	510	(600-1½)

OKLAHOMA CITY, OK

Amdt 2A, 07APR11 (11153) (FAA)

ELEV 1299

WILEY POST (PWA)

RADAR-1 124.6 266.8 

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	35R		AB D	1840-1 1840-1¾	541 541	(600-1) (600-1¾)	C	1840-1½	541	(600-1½)
CIRCLING	ALL RWY		AB D	1840-1 1880-2	541 581	(600-1) (600-2)	C	1840-1½	541	(600-1½)

10 OCT 2019 to 07 NOV 2019

10 OCT 2019 to 07 NOV 2019

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

19171

RADAR INSTRUMENT APPROACH MINIMUMS

OKLAHOMA CITY, OK

Amdt 21A, 13OCT16 (16287) (FAA)

ELEV 1296

WILL ROGERS WORLD (OKC)

RADAR-1 124.6 266.8 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
ASR	17L		ABCDE	1680/40	393	(400-¾)
	35R		ABCDE	1680/40	386	(400-¾)
	17R		ABCDE	1680/40	398	(400-¾)
	35L		ABCDE	1680/40	404	(500-¾)
CIRCLING	ALL RWY		A	1740-1¼	444	(500-1¼)
			B	1760-1¼	464	(500-1¼)
			C	1960-1¼	664	(700-1¼)
			D	2000-2¼	704	(800-2¼)
			E	2240-3	944	(1000-3)

For inoperative MALSR, increase S-17L, S-17R, and S-35L CAT E visibility to 1¼.

For inoperative ALSF, increase S-35R CAT E visibility to 1¼.

10 OCT 2019 to 07 NOV 2019

10 OCT 2019 to 07 NOV 2019

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

TINKER AFB (KTIK), (Oklahoma City) OK (12320 USAF)

ELEV **1291**

RADAR - CTC OKLAHOMA CITY APP CON (E) 118.95 118.3 323.1 273.525



	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u>	<u>HAT/</u>	<u>CEIL-VIS</u>
				<u>MDA-VIS</u>	<u>HATh/</u>	
ASR	36 ¹		A	1940/24	649	(700-½)
			B	1940/40	649	(700-¾)
			C	1940/60	649	(700-1¼)
			D	1940-1½	649	(700-1½)
			E	1940-1¾	649	(700-1¾)
	18 ²		A	2000/40	733	(800-¾)
			B	2000/50	733	(800-1)
			C	2000-1¾	733	(800-1¾)
			D	2000-2	733	(800-2)
			E	2000-2¼	733	(800-2¼)
CIR ³	36		A	1940-1	649	(700-1)
			B	1940-1¼	649	(700-1¼)
			C	1940-1¾	649	(700-1¾)
			D	1980-2¼	689	(700-2¼)
			E	2040-2¾	749	(800-2¾)
	18		A	2000-1	709	(800-1)
			B	2000-1¼	709	(800-1¼)
			C	2000-2	709	(800-2)
			D	2000-2¼	709	(800-2¼)
			E	2040-2¾	749	(800-2¾)

¹When ALS inop, increase CAT A RVR to 50 and vis to 1 mile, CAT B RVR to 60 and vis to 1¼ miles, CAT C vis to 1¾ miles, CAT D vis to 2 miles, CAT E vis to 2¼ miles.

²When ALS inop, increase CAT A RVR to 50 and vis to 1 mile, CAT B RVR to 60 and vis to 1¼ miles, CAT C vis to 2 miles, CAT D vis to 2¼ miles, CAT E vis to 2½ miles.

³CAT E circling not authorized in sector S of Rwy 13-31 and W of Rwy 18-36.

10 OCT 2019 to 07 NOV 2019

10 OCT 2019 to 07 NOV 2019

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

19171

N5

RADAR INSTRUMENT APPROACH MINIMUMS

TULSA, OK

Amdt 18, 13JAN11 (15008) (FAA)

ELEV 677

TULSA INTL (TUL)

RADAR-1 124.0 338.3 **▽ ▲**

ASR	RWY	GP/TCH/RPI	CAT	DA/	HAT/	CEIL-VIS	CAT	DA/	HAT/	CEIL-VIS
				MDA-VIS	HAA			MDA-VIS	HAA	
26			AB	1060-1	409	(400-1)	CD	1060-1¼	409	(400-1¼)
			E	1060-1½	409	(400-1½)				
18L			AB	1080/24	439	(500-½)	C	1080/40	439	(500-¾)
			DE	1080/50	439	(500-1)				
36R			AB	1140/24	490	(500-½)	C	1140/40	490	(500-¾)
			D	1140/50	490	(500-1)				
18R			AB	1080-1	413	(500-1)	CD	1080-1¼	413	(500-1¼)
			E	NA						
8			AB	1120-1	449	(500-1)	C	1120-1¼	449	(500-1¼)
			DE	1120-1½	449	(500-1½)				
36L			AB	1180-1	503	(600-1)	CD	1180-1½	503	(600-1½)
			E	NA						
CIRCLING	ALL RWY		AB	1180-1	503	(600-1)	C	1180-1½	503	(600-1½)
			D	1300-2	623	(700-2)				

Circling NA for CAT E South of runway 8-26.

10 OCT 2019 to 07 NOV 2019

10 OCT 2019 to 07 NOV 2019

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

19171

N5

SC-1