

# RADAR MINS


20142


N1

## RADAR INSTRUMENT APPROACH MINIMUMS

### JACKSONVILLE NAS (KNIP), (TOWERS FIELD) FL (Amdt 5, 19283 USN)

ELEV 23

RADAR<sup>1</sup> - (E) 127.7x 133.25 266.8x 276.4x 282.375 328.4 348.0x 363.0x 379.225x 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATth</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR <sup>1</sup>	10 <sup>25</sup> 28 <sup>2 310</sup>	3.0°/40/792 3.0°/40/750	ABCDE ABCDE	121-¼ 113-¼	100 100	(100-¼) (100-¼)
PAR W/O GS <sup>1</sup>	10 <sup>4</sup> 28 <sup>411</sup>		ABCDE ABCDE	400-5/8 340-¾	379 327	(400-5/8) (400-¾)
ASR	28 <sup>89</sup>  10 <sup>88</sup> 32 <sup>7</sup>		AB CDE ABCDE AB CDE	400-¾ 400-7/8 440-¾ 460-1¼ 460-1¾	387 387 419 450 450	(400-¾) (400-7/8) (500-¾) (500-1¼) (500-1¾)
 CIR	ALL RWY		AB C D E	500-1¼ 560-1½ 800-2½ 920-3	477 537 777 897	(500-1¼) (600-1½) (800-2½) (900-3)

<sup>1</sup>No-NOTAM MP: PAR 1200-1600Z++ Tue.

<sup>2</sup>When ALS inop, increase vis CAT ABCDE to ½ mile.

<sup>3</sup>CAUTION: Wheel Crossing Height (WCH) for aircraft similar to B-747/767/720/757, DC-10, A-300, KC-10, E-4, C-5, and VC-25 is 15 ft.

<sup>4</sup>When ALS inop, increase vis CAT ABCDE to 1½ miles.

<sup>5</sup>Rwy 10 VGS1 and PAR glidepath not coincident VGS1 angle 3.00/TCH 51.

<sup>6</sup>When ALS inop, increase CAT ABCDE vis to 1¼ miles.

<sup>7</sup>Step Down Fix at 2 NM from thld, 660 min.

<sup>8</sup>ASR Rwy 10 and 28, Step Down Fix at 2 NM from thld, 700 min.

<sup>9</sup>When ALS inop, increase CAT AB vis to 1 mile; CAT CDE vis to 1½ miles.

<sup>10</sup>Rwy 28 VGS1 and PAR glidepath not coincident VGS1 angle 3.00/TCH 62.

<sup>11</sup>Step Down Fix at 2 NM from RPI, 660 min.

21 MAY 2020 to 18 JUN 2020


21 MAY 2020 to 18 JUN 2020

### KEY WEST, FL

Amdt 5, 19SEP13 (14149) (FAA)

ELEV 3

### KEY WEST INTL (EYW)

RADAR-1 124.025 313.7 

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	27		AB	440-1	437	(500-1)	CD	440-1¼	437	(500-1¼)
	9		AB	460-1	457	(500-1)	C	460-1¾	457	(500-1¾)
CIRCLING	ALL RWY		AB D	500-1 620-2	497 617	(500-1) (700-2)	C	620-1¾	617	(700-1¾)

ASR S-9: Circling to Rwy 27 NA at night.

ASR S-9: Helicopter visibility reduction below ¾ SM NA.

ASR S-27: Helicopter visibility reduction below 1 SM NA.

ASR S-27: Straight-in and circling minimums NA at night.

SE-3

## RADAR INSTRUMENT APPROACH MINIMUMS

# RADAR MINS


20142



N1

**RADAR INSTRUMENT APPROACH MINIMUMS**

**KEY WEST NAS (KNQX), (BOCA CHICA FLD), FL (Amdt 2, 20142 USN)**

ELEV 6

**RADAR<sup>1</sup> - (E) 134.925x 284.67x 348.25x 317.575x** 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATh/</u> <u>HAT/</u>	<u>CEIL-VIS</u>
PAR <sup>2</sup>	8 <sup>3,8</sup>	3.0 <sup>7</sup> /43/813	ABCDE	<b>104</b> - <sup>1</sup> / <sub>4</sub>	100	(100- <sup>1</sup> / <sub>4</sub> )
	4 <sup>9</sup>	3.0 <sup>7</sup> /35/656	ABCDE	<b>104</b> - <sup>1</sup> / <sub>2</sub>	100	(100- <sup>1</sup> / <sub>2</sub> )
	26	3.0 <sup>7</sup> /45/849	ABCDE	<b>106</b> - <sup>1</sup> / <sub>2</sub>	100	(100- <sup>1</sup> / <sub>2</sub> )
PAR W/O GS	4 <sup>13</sup>		ABCDE	<b>300</b> -1 <sup>1</sup> / <sub>8</sub>	296	(300-1 <sup>1</sup> / <sub>8</sub> )
	26		ABCDE	<b>340</b> -1	334	(400-1)
	8 <sup>4,13</sup>		AB	<b>440</b> - <sup>5</sup> / <sub>8</sub>	436	(500- <sup>5</sup> / <sub>8</sub> )
			CDE	<b>440</b> - <sup>3</sup> / <sub>4</sub>	436	(500- <sup>3</sup> / <sub>4</sub> )
ASR	32 <sup>11</sup>		ABCDE	<b>340</b> -1 <sup>1</sup> / <sub>4</sub>	336	(400-1 <sup>1</sup> / <sub>4</sub> )
	4 <sup>11</sup>		ABCDE	<b>340</b> -1 <sup>1</sup> / <sub>4</sub>	336	(400-1 <sup>1</sup> / <sub>4</sub> )
	8 <sup>5,12</sup>		ABCDE	<b>420</b> - <sup>3</sup> / <sub>4</sub>	416	(500- <sup>3</sup> / <sub>4</sub> )
	14		ABCDE	<b>420</b> -1 <sup>1</sup> / <sub>4</sub>	416	(500-1 <sup>1</sup> / <sub>4</sub> )
	22 <sup>10</sup>		AB	<b>460</b> -1 <sup>1</sup> / <sub>4</sub>	454	(500-1 <sup>1</sup> / <sub>4</sub> )
			CDE	<b>460</b> -1 <sup>1</sup> / <sub>8</sub>	454	(500-1 <sup>1</sup> / <sub>8</sub> )
	26		AB	<b>460</b> -1 <sup>1</sup> / <sub>4</sub>	454	(500-1 <sup>1</sup> / <sub>4</sub> )
		CDE	<b>460</b> -1 <sup>1</sup> / <sub>8</sub>	454	(500-1 <sup>1</sup> / <sub>8</sub> )	
 CIR <sup>6,7</sup> PAR W/O GS	4, 8, 26		A	<b>460</b> -1 <sup>1</sup> / <sub>8</sub>	454	(500-1 <sup>1</sup> / <sub>8</sub> )
			B	<b>500</b> -1 <sup>1</sup> / <sub>8</sub>	494	(500-1 <sup>1</sup> / <sub>8</sub> )
			C	<b>500</b> -1 <sup>1</sup> / <sub>2</sub>	494	(500-1 <sup>1</sup> / <sub>2</sub> )
			DE	<b>560</b> -2	554	(600-2)
 CIR ASR			A	<b>460</b> -1 <sup>1</sup> / <sub>4</sub>	454	(500-1 <sup>1</sup> / <sub>4</sub> )
			B	<b>500</b> -1 <sup>1</sup> / <sub>4</sub>	494	(500-1 <sup>1</sup> / <sub>4</sub> )
			C	<b>500</b> -1 <sup>1</sup> / <sub>2</sub>	494	(500-1 <sup>1</sup> / <sub>2</sub> )
			DE	<b>560</b> -2	554	(600-2)

21 MAY 2020 to 18 JUN 2020

21 MAY 2020 to 18 JUN 2020

<sup>1</sup>Opr 1200-0300Z++.

<sup>2</sup>No NOTAM preventative maint sked: PAR 1300-1700Z++ Mon.

<sup>3</sup>When ALS inop, increase vis CAT ABCDE to 1/2 mile.

<sup>4</sup>When ALS inop, increase vis CAT AB to 1 mile, CDE to 1/4 miles.

<sup>5</sup>When ALS inop, increase vis CAT ABCDE to 1/4 miles.

<sup>6</sup>When circling from PAR W/O GS Rwy 4, increase CAT AB vis to 1/8 miles.

<sup>7</sup>When VGSI inop, circling not authorized to Rwy 14 and 22 at night.

<sup>8</sup>WCH (Group 4: 18 ft) is less than the minimum height (20).

<sup>9</sup>WCH (Group 3: 16 ft, Group 4: 11 ft) is less than the minimum height (20).

<sup>10</sup>34:1 visual area penetration by powerline up to 118' MSL, 3000' from thld; Roadway plus vehicle 713'

from thld up to 21' MSL. Visibility reduction by copters not authorized.

<sup>11</sup>SDF at 2 NM from thld at or above 640' MSL.

<sup>12</sup>SDF at 2 NM from thld at or above 680' MSL.


<sup>13</sup>SDF at 2 NM from touchdown at or above 640' MSL.


**RADAR INSTRUMENT APPROACH MINIMUMS**

**RADAR INSTRUMENT APPROACH MINIMUMS**

**MAYPORT NS (KNRB), (ADM DAVID L. MC DONALD FLD), FL (Amdt 3, 20142 USN)**

**ELEV 15**

**RADAR<sup>1 2</sup> - (E) 119.7x 125.525x 253.95x 257.875x 323.25x 355.6x 377.175 379.025x **

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR	5	3.0°/48/887	ABCDE	<b>212-¾</b>	200	(200-¾)
	23 <sup>3 4</sup>	3.0°/50/937	ABCDE	<b>322-1</b>	307	(400-1)
	COP 5 <sup>5</sup>	3.0°/48/887	COPTER	<b>167-½</b>	155	(200-½)
	COP 23 <sup>4 5</sup>	3.0°/50/937	COPTER	<b>322-1</b>	307	(400-1)
PAR W/O GS	5 <sup>8</sup>		AB	<b>400-1</b>	388	(400-1)
			CDE	<b>400-1½</b>	388	(400-1½)
	23 <sup>4</sup>		AB	<b>420-1</b>	405	(500-1)
		CDE	<b>420-1½</b>	405	(500-1½)	
ASR	5 <sup>7</sup>		AB	<b>440-1</b>	428	(500-1)
			CDE	<b>440-1¼</b>	428	(500-1¼)
	23 <sup>4</sup>		AB	<b>520-1</b>	505	(600-1)
			CDE	<b>520-1½</b>	505	(600-1½)
 CIR PAR W/O GS ASR	5-23 <sup>4 6</sup>		AB	<b>560-1</b>	545	(600-1)
			C	<b>560-1½</b>	545	(600-1½)
			D	<b>640-2</b>	625	(700-2)
			E	<b>640-2¼</b>	625	(700-2¼)

<sup>1</sup>SFA not avbl.

<sup>2</sup>No-NOTAM preventive maint ASR 1100-1500Z++ Tue., PAR 1100-1500Z++ Wed.

<sup>3</sup>Procedure is authorized only when the St. Johns River is clear of vessels from the mouth of Haulover Creek to St. Johns Point. ATC will advise aircraft on final approach if a conflict is present and coordinate a missed approach as required. Does not apply to practice approaches in VMC.

<sup>4</sup>Vessels with masts up to 150' transitioning the St. Johns River within 1 NM of Rwy 23 THLD.

<sup>5</sup>NOT FOR CIVIL USE.

<sup>6</sup>CAUTION: When Rwy 23 VGSI inop, circling to Rwy 23 NA at night, unless station has an approved observer monitoring marine traffic in the St. Johns River channel.

<sup>7</sup>Step Down Fix at 3 NM from THLD, 1020 min.

<sup>8</sup>Step Down Fix at 2 NM from touchdown, 640 min.

21 MAY 2020 to 18 JUN 2020

21 MAY 2020 to 18 JUN 2020

**RADAR INSTRUMENT APPROACH MINIMUMS**

**RADAR INSTRUMENT APPROACH MINIMUMS**

**PENSACOLA NAS (KNPA),** (FORREST SHERMAN FLD), FL (Amdt 3, 19227 USN)  
**RADAR<sup>1</sup> - (E)** 128.25 239.05 285.625 288.325 305.2 314.0 318.8 348.725 383.8 **▼**

**ELEV 28**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HAT<sub>h</sub></u>	<u>CEIL-VIS</u>	
PAR	7L <sup>2</sup>	3.0°/58/1124	ABCDE	<b>123</b> -½	100	(100-½)	
	1 <sup>7</sup>	3.0°/39/750	ABCDE	<b>128</b> -½	100	(100-½)	
	7R	3.0°/57/1085	ABCDE	<b>125</b> -½	100	(100-½)	
	19 <sup>3</sup>	3.0°/38/692	ABCDE	<b>122</b> -½	100	(100-½)	
	25L <sup>7</sup>	3.0°/39/748	ABCDE	<b>122</b> -½	100	(100-½)	
	25R <sup>8</sup>	3.0°/38/711	ABCDE	<b>121</b> -½	100	(100-½)	
PAR W/O GS	7L <sup>3</sup>		ABCDE	<b>360</b> -½	337	(400-½)	
	7R		ABCDE	<b>360</b> -1	335	(400-1)	
	1		ABCDE	<b>360</b> -1½	332	(400-1½)	
	19		ABCDE	<b>400</b> -1½	378	(400-1½)	
	25L		AB	<b>440</b> -1	418	(500-1)	
	25R		CDE	<b>440</b> -1½	418	(500-1½)	
PAR W/O GS SIDESTEP	25R		AB	<b>440</b> -1	419	(500-1)	
			CDE	<b>440</b> -1½	419	(500-1½)	
	7R		ABCDE	<b>360</b> -1	335	(400-1)	
ASR	25L		AB	<b>440</b> -1	418	(500-1)	
			CDE	<b>440</b> -1½	418	(500-1½)	
	7L <sup>4</sup>		AB	<b>500</b> -¾	477	(500-¾)	
ASR SIDESTEP			CDE	<b>500</b> -1	477	(500-1)	
	1		ABCDE	<b>460</b> -1¼	432	(500-1¼)	
	7R		AB	<b>500</b> -1¼	475	(500-1¼)	
			CDE	<b>500</b> -1¾	475	(500-1¾)	
	19		AB	<b>500</b> -1¼	478	(500-1¼)	
			CDE	<b>500</b> -1¾	478	(500-1¾)	
	25L		AB	<b>480</b> -1¼	458	(500-1¼)	
			CDE	<b>480</b> -1¾	458	(500-1¾)	
	25R		AB	<b>480</b> -1¼	459	(500-1¼)	
			CDE	<b>480</b> -1¾	459	(500-1¾)	
	ASR SIDESTEP	7R <sup>5</sup>		AB	<b>500</b> -1¼	475	(500-1¼)
				CDE	<b>500</b> -1¾	475	(500-1¾)
25L <sup>6</sup>			AB	<b>480</b> -1¼	458	(500-1¼)	
			CDE	<b>480</b> -1¾	458	(500-1¾)	

(CONTINUED ON NEXT PAGE)

21 MAY 2020 to 18 JUN 2020

21 MAY 2020 to 18 JUN 2020

**RADAR INSTRUMENT APPROACH MINIMUMS**

**RADAR INSTRUMENT APPROACH MINIMUMS**

**PENSACOLA NAS (KNPA) (CONT'D)**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
CIR ASR			AB	<b>520-1¼</b>	492	(500-1¼)
			C	<b>540-1½</b>	512	(600-1½)
			DE	<b>580-2</b>	552	(600-2)
CIR PAR W/O GS			AB	<b>520-1½</b>	492	(500-1½)
			C	<b>540-1½</b>	512	(600-1½)
			DE	<b>580-2</b>	552	(600-2)

<sup>1</sup>No-NOTAM MP: PAR 1400-1800Z++ Sat.

<sup>2</sup>When ALS inop, increase vis CAT ABCDE to ½ mile.

<sup>3</sup>When ALS inop, increase vis CAT ABCDE to 1 mile.

<sup>4</sup>When ALS inop, increase vis CAT AB to 1¼ miles, CAT CDE to 1¾ miles.

<sup>5</sup>Sidestep within 2.5 DME of NPA TACAN (1.73 NM from THLD).

<sup>6</sup>Sidestep within 2.5 DME of NPA TACAN (1.94 NM from THLD).

<sup>7</sup>CAUTION: Wheel Crossing Height (WCH) for Group 3 (19 ft) and Group 4 (14 ft) is less than 20 ft.

<sup>8</sup>CAUTION: Wheel Crossing Height (WCH) for Group 3 (18 ft) and Group 4 (13 ft) is less than 20 ft.

21 MAY 2020 to 18 JUN 2020

**TALLAHASSEE, FL**

Amdt 6B, 20JUN2019 (19171) (FAA)

ELEV 83

**TALLAHASSEE INTL (TLH)**

**RADAR-1** 135.8 317.4 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	36		AB	<b>460/24</b>	398	(400-½)	CD	<b>460/35</b>	398	(400-¾)
	27		AB	<b>480/24</b>	422	(500-½)	CD	<b>480/40</b>	422	(500-¾)
	9		AB	<b>500/55</b>	435	(500-1¼)	CD	<b>500-1¼</b>	435	(500-1¼)
	18		AB	<b>560-1</b>	477	(500-1)	CD	<b>560-1¾</b>	477	(500-1¾)
CIRCLING	ALL RWY		A	<b>580-1</b>	497	(500-1)	B	<b>600-1</b>	517	(600-1)
			C	<b>640-1½</b>	557	(600-1½)	D	<b>800-2¼</b>	717	(800-2¼)

When control tower closed, ASR NA.

Rwy 9 helicopter visibility reduction below RVR 4000 not authorized.

21 MAY 2020 to 18 JUN 2020

**RADAR INSTRUMENT APPROACH MINIMUMS**

**RADAR INSTRUMENT APPROACH MINIMUMS**

**TYNDALL AFB (KPAM)**, (Panama City) FL Amdt 2, 21MAY20 (20142) (USAF)

ELEV 17

**RADAR<sup>2</sup> - (E)** 125.2 392.1 (N above 5000') 120.825 379.3 (N below 5000') 124.15 338.35 (S above 5000') 119.775 317.45 (S below 5000') **▼**

	<b>RWY</b>	<b>GS/TCH/RPI</b>	<b>CAT</b>	<b>DH/ MDA-VIS</b>	<b>HAT/ HATh/ HAA</b>	<b>CEIL-VIS</b>
PAR <sup>1</sup>	14L <sup>3</sup>	2.5°/50/1182	ABCDE	<b>214/24</b>	200	(200-½)
	32R <sup>3</sup>	2.5°/50/1145	ABCDE	<b>214/24</b>	200	(200-½)
	14R <sup>3</sup>	2.5°/36/815	ABCDE	<b>215-¾</b>	200	(200-¾)
	32L <sup>6</sup>	2.5°/41/940	ABCDE	<b>217-¾</b>	200	(200-¾)
ASR <sup>1</sup>	32R <sup>4</sup>		AB	<b>460/24</b>	446	(500-½)
			CDE	<b>460/45</b>	446	(500-¾)
	32L		AB	<b>460-1</b>	443	(500-1)
			CDE	<b>460-1¾</b>	443	(500-1¾)
	14L <sup>4</sup>		AB	<b>480/24</b>	466	(500-½)
			CDE	<b>480/50</b>	466	(500-1)
14R			AB	<b>480-1</b>	465	(500-1)
			CDE	<b>480-1¾</b>	465	(500-1¾)
<b>C</b> CIR	All Rwy		AB	<b>540-1</b>	523	(600-1)
			C	<b>560-1½</b>	543	(600-1½)
			D	<b>580-2</b>	563	(600-2)
			E	<b>620-2¼</b>	603	(700-2¼)

<sup>1</sup> When ASR out PAR not avbl.

<sup>2</sup> No-NOTAM preventive maint sked: DASR/STARS 0930-1130Z++ Mon-Fri. PAR 1200-1400Z++ Mon-Fri.

<sup>3</sup> When ALS inop, increase RVR to 40 and vis to ¾ mile.

<sup>4</sup> When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE vis to 1¾ miles.

<sup>5</sup> CAUTION: Height Group 3 WCH 16', Height Group 4 WCH 11'.

<sup>6</sup> CAUTION: Height Group 4 WCH 16'.

21 MAY 2020 to 18 JUN 2020

21 MAY 2020 to 18 JUN 2020

**WHITING FLD NAS-NORTH (KNSE)**, FL (Milton) (Amdt 5, 20030 USN)

ELEV 199

**RADAR<sup>1</sup> - Ctc PENSACOLA APP CON (E)** 126.85 127.35 278.8 298.9 **▼**

	<b>RWY</b>	<b>GS/TCH/RPI</b>	<b>CAT</b>	<b>DH/ MDA-VIS</b>	<b>HAT/ HATh/ HAA</b>	<b>CEIL-VIS</b>
ASR	14 <sup>2 4 5 6</sup>		ABCDE	<b>560-¾</b>	361	(400-¾)
	23 <sup>4</sup>		ABCDE	<b>540-1¼</b>	357	(400-1¼)
	5 <sup>4 5</sup>		AB	<b>640-1¼</b>	460	(500-1¼)
			CDE	<b>640-1¾</b>	460	(500-1¾)
<b>C</b> CIR <sup>3</sup>	5, 14, 23, 32		A	<b>640-1¼</b>	460	(500-1¼)
			B	<b>680-1¼</b>	481	(500-1¼)
			C	<b>680-1½</b>	481	(500-1½)
			DE	<b>760-2</b>	561	(600-2)

<sup>1</sup>No-NOTAM preventive maint sked: Mon 1300-1800Z++; Apch only avbl dur NDZ opr hr.

<sup>2</sup>When ALS inop, increase vis CAT ABCDE to 1¼ miles.

<sup>3</sup>Circling not authorized in sector SE of Rwy 5-23 and SW of Rwy 14-32.

<sup>4</sup>Vertical Descent Angle not coincident with VGSI angle.

<sup>5</sup>Step Down Fix at 3 NM from thld, 1000 min.

<sup>6</sup>Step Down Fix at 2 NM from thld, 880 min.

SE-3


**RADAR INSTRUMENT APPROACH MINIMUMS**

**RADAR INSTRUMENT APPROACH MINIMUMS**

**WHITING FLD NAS-SOUTH (KNDZ)**, FL (Milton) (Amdt 5, 19311 USN)

ELEV 177

**RADAR<sup>1</sup>** - Ctc PENSACOLA APP CON (E) 124.85 385.4 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATh/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR	32 23 <sup>2</sup>	3.0 <sup>7</sup> /58/1030 3.0 <sup>7</sup> /41/672	ABCDE ABCDE	<b>283</b> - <sup>1</sup> / <sub>2</sub> <b>428</b> - <sup>7</sup> / <sub>8</sub>	111 250	(100- <sup>1</sup> / <sub>2</sub> ) (300- <sup>7</sup> / <sub>8</sub> )
PAR W/O GS	32 <sup>3,7</sup> 23 <sup>8</sup>		ABCDE ABCDE	<b>420</b> - <sup>5</sup> / <sub>8</sub> <b>520</b> - <sup>1</sup> / <sub>4</sub>	248 342	(300- <sup>5</sup> / <sub>8</sub> ) (400- <sup>1</sup> / <sub>4</sub> )
ASR	32 <sup>9</sup> 23 <sup>6,9</sup> 14 <sup>4</sup> 5 <sup>10</sup>		ABCDE ABCDE AB CDE AB CDE	<b>560</b> - <sup>3</sup> / <sub>4</sub> <b>540</b> - <sup>1</sup> / <sub>4</sub> <b>640</b> - <sup>1</sup> / <sub>4</sub> <b>640</b> - <sup>1</sup> / <sub>8</sub> <b>640</b> - <sup>1</sup> / <sub>4</sub> <b>640</b> - <sup>1</sup> / <sub>8</sub>	388 362 464 464 470 470	(400- <sup>3</sup> / <sub>4</sub> ) (400- <sup>1</sup> / <sub>4</sub> ) (500- <sup>1</sup> / <sub>4</sub> ) (500- <sup>1</sup> / <sub>8</sub> ) (500- <sup>1</sup> / <sub>4</sub> ) (500- <sup>1</sup> / <sub>8</sub> )
 CIR	<b>All Rwys<sup>5</sup></b>		A B C DE	<b>640</b> - <sup>1</sup> / <sub>4</sub> <b>660</b> - <sup>1</sup> / <sub>4</sub> <b>680</b> - <sup>1</sup> / <sub>2</sub> <b>740</b> -2	462 482 502 562	(500- <sup>1</sup> / <sub>4</sub> ) (500- <sup>1</sup> / <sub>4</sub> ) (600- <sup>1</sup> / <sub>2</sub> ) (600-2)

<sup>1</sup>No-NOTAM preventive maint sked: Mon 1300-1700Z++.

<sup>2</sup>CAUTION: PAR TCH and RPI not coincident with PAPI.

<sup>3</sup>When ALS inop, increase vis CAT ABCDE to 1 mile.

<sup>4</sup>20:1 visual area penetrated by unlit obstacles. Night straight-in and circling procedures are not authorized to this runway.

<sup>5</sup>Circling not authorized in sector NE of Rwy 14-32 and NW of Rwy 5-23. Circling authorized from PAR W/O GS and ASR only. Caution - Whiting Fld NAS - North 1 NM North.

<sup>6</sup>When ALS inop, increase vis CAT ABCDE to 1 1/4 miles.

<sup>7</sup>Step Down Fix at 3 NM from TD, 1000 min.

<sup>8</sup>Step Down Fix at 2 NM from TDF, 700 min.

<sup>9</sup>Step Down Fix at 3 NM from thld, 1100 min.

<sup>10</sup>Step Down Fix at 2 NM from thld, 880 min.

21 MAY 2020 to 18 JUN 2020

21 MAY 2020 to 18 JUN 2020

**RADAR INSTRUMENT APPROACH MINIMUMS**