

WAAS CH 78437 W35B	APP CRS 355°	Rwy ldg TDZE Apt Elev	5001 1275 1300
--	------------------------	-----------------------------	---



RNAV (GPS) RWY 35L

WILEY POST (PWA)


ASR DME/DME RNP-0.3 NA. VDP NA when using Will Rogers World altimeter setting. When local altimeter setting not received, use Will Rogers World altimeter setting and increase all MDA 40 feet; increase LP Cat C/D visibility 1/8 mile and Circling Cat C 1/4 mile.

MISSED APPROACH: Climb to 1700 then climbing left turn to 3400 direct IFI VORTAC and hold.

ATIS 128.725	OKC CITY APP CON 124.6 266.8	WILEY POST TOWER ★ 126.9(CTAF) 306.9	GND CON 121.7	UNICOM 122.95
------------------------	--	--	-------------------------	-------------------------



ELEV 1300	D	TDZE 1275
-----------	----------	-----------



1700	3400	IFI	WIGOK	YOCU	4 NM Holding Pattern
ZEROK 1.6 NM to RW35L		1820	2900	2900	2900
RW35L 1.1 NM to RW35L		3.00° TCH 45	355°	175°	355°
1.1 NM	0.5 NM	3.4 NM	3.3 NM		
CATEGORY	A	B	C	D	
LP MDA	1660-1	385 (400-1)	1660-1 ¹ / ₈	385 (400-1 ¹ / ₈)	
LNAV MDA	1720-1	445 (500-1)	1720-1 ³ / ₈	445 (500-1 ³ / ₈)	
C CIRCLING	1780-1	480 (500-1)	1880-1 ¹ / ₂ 580 (600-1 ¹ / ₂)	1880-2 580 (600-2)	

SC-1, 18 JUN 2020 to 16 JUL 2020

SC-1, 18 JUN 2020 to 16 JUL 2020