

TAKEOFF MINIMUMS

Rwys 8L/R: Standard.

Rwys 1L/R: Standard with minimum climb of 400' per NM to 5200.

Rwys 19L/R, 26L/R: Standard with minimum climb of 360' per NM to 7000.

NOTE: RADAR and DME required.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 1L/R: Climb heading 014° to 2500, then climbing right turn heading 050°, thence. . . .

TAKEOFF RUNWAYS 8L/R: Climb heading 079°, thence. . . .

TAKEOFF RUNWAYS 19L/R: Climb heading 194° until LAS VORTAC 3 DME, then climbing right turn heading 220°, thence. . . .

TAKEOFF RUNWAYS 26L/R: Climb heading 259° until LAS VORTAC 3 DME, then climbing left turn heading 190°, thence . . . .

. . . . RADAR vectors to transition or assigned route. Maintain 7000, expect clearance to filed altitude two minutes after departure.

LOST COMMUNICATIONS: If no contact with ATC upon reaching 7000, proceed direct BLD VORTAC then climb in BLD VORTAC holding pattern to appropriate MEA for route of flight.

DOVE CREEK TRANSITION (LAS5.DVC): From over TRALR on LAS R-066 to NICLE, then on PGA R-234 to PGA VOR/DME, then on PGA R-053 and DVC R-233 to DVC VORTAC.

SW-4, 16 JUL 2020 to 13 AUG 2020
SW-4, 16 JUL 2020 to 13 AUG 2020