RNAV (GPS) RWY 15

NASA SHUTTLE LANDING FACILITY (TTS)

WAAS	APP CRS	Rwy Idg 15001
CH 50534	155°	TDZE 8
W15A		Apt Elev 9

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Inop table does not apply.

ALSF-2

MISSED APPROACH: Climb to 800, then climbing left turn to 2500 direct EARTH and hold.

ORLANDO APP CON	NASA TOWER ★	GND CON
134.95 281.425	128.55 (CTAF) 284.0	121.75

RADAR REQUIRED

9 NM
060°
240°
2500
240°
(6)
(IF)
ROCIT
(IAF)
EARTH
Max 250K
1500
155°
(6.1)
(FAF)
STARS
105 ±
RW15
508
397
582
MSA RW15 25 NM
3000
R-2935
R-2934
R-2932
R-2933
CAPE CANAVERAL AFS SKID STRIP

ELEV 9 TDZE 8
155° to RW15
TWR 107
15001 X 300
33

ROCIT
2500
155°
STARS
1500
1500
GP 3.00°
TCH 55
RW15
800
EARTH
*LNAV only
*0.9 NM to RW15
6.1 NM
3.6 NM
0.9 NM

CATEGORY	A	B	C	D	E
LPV DA	208-1		200 (200-1)		
LNAV/VNAV DA	286-1		278 (300-1)		
LNAV MDA	360-1		352 (400-1)		
C CIRCLING	420-1 411 (500-1)	460-1 451 (500-1)	940-2¾ 931 (1000-2¾)	940-3	931 (1000-3)

HIRL Rwy 15-33

SE-3, 16 JUL 2020 to 13 AUG 2020
SE-3, 16 JUL 2020 to 13 AUG 2020