

LOC/DME I-OMO 111.55 Chan 52 (Y)	APP CRS 095°	Rwy Ldg 9000 TDZE 1000 Apt Elev 1026
--	------------------------	---

ILS or LOC RWY 10


HARTSFIELD-JACKSON ATLANTA INTL (ATL)

▼ For inop ALSF-2, increase S-LOC Cats C/D visibility to 1 1/2%.
 Simultaneous approach authorized with Rwy 9L or 8R or 8L, or Rwys 9L and 8L.
 DME or Radar required.
 Localizer not suitable for electronic rollout guidance.




MISSED APPROACH: Climb to 1400 then climbing right turn to 3000 on ATL VORTAC R-185 to SCARR INT/ATL 15 DME and hold.

D-ATIS ARR 119.65	ATLANTA APP CON 127.9 379.9	ATLANTA TOWER 8L-26R 8R-26L 9L-27R 9R-27L 10-28 RWYS 119.1 125.325 123.85 119.3 119.5 254.4	ALL RWYS 121.9	GND CON DEL 121.75	ALL RWYS 121.65 254.4
-----------------------------	--	--	-----------------------------	---------------------------------	------------------------------------




SE-4, 10 SEP 2020 to 08 OCT 2020

SE-4, 10 SEP 2020 to 08 OCT 2020



ELEV	1026	TDZE	1000
------	------	------	------

CATEGORY	A	B	C	D
S-ILS 10	1200/18		200 (200-1/2)	
S-LOC 10	1500/24	500 (500-1/2)	1500/50	500 (500-1)



FAF to MAP 5.2 NM					
Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44