




APP CRS <b>058°</b>	Rwy Idg <b>9000</b>
	TDZE <b>773</b>
	Apt Elev <b>799</b>

# RNAV (RNP) Z RWY 6L

CLEVELAND-HOPKINS INTL (CLE)

RNP AR APCH.	<p>For uncompensated Baro-VNAV systems, procedure NA below -18°C (0°F) or above 54°C (130°F). For inop ALS, increase RNP 0.17 all Cats visibility to RVR 5500 and RNP 0.30 all Cats visibility to RVR 6000.</p>	<p>ALSIF-2</p>	<p>MISSED APPROACH: Climb to 3000 direct ACAPO and on track 001° to PASLE and hold.</p>
--------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------	-----------------------------------------------------------------------------------------

D-ATIS ARR <b>127.85</b> DEP <b>132.375</b>	CLEVELAND APP CON <b>124.0 346.325</b>	CLEVELAND TOWER <b>124.5 273.45</b>	GND CON <b>121.7 273.45</b>	CLNC DEL <b>125.05 273.45</b>	CPDLC
---------------------------------------------------	-------------------------------------------	----------------------------------------	--------------------------------	----------------------------------	-------



CATEGORY	A	B	C	D
RNP 0.17 DA		1123/30	350 (400-5/8)	
RNP 0.30 DA		1176/40	403 (400-3/4)	

**AUTHORIZATION REQUIRED**

REIL Rwy 10  
TDZ/CL Rwy 6L, 6R, 24L, and 24R  
HIRL Rwy 6L-24R, 6R-24L and 10-28

EC-2, 10 SEP 2020 to 08 OCT 2020

EC-2, 10 SEP 2020 to 08 OCT 2020