ILS or LOC RWY 32

DOTHAN RGNL (DHN)

LOC I-DHN	APP CRS	Rwy Idg	8496
108.3	318°	TDZE	382
		Apt Elev	401

For inoperative MALSR, increase S-LOC 32 Cat C/D visibility to 2½ miles.
** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 1000 then climbing right turn to 3000 on hdg 130° and RRS VORTAC R-089 to BLALY INT/RRS 19.8 DME and hold.

ATIS	CAIRNS APP CON★	DOTHAN TOWER ★	GND CON	UNICOM
135.725	125.4 327.125	118.4 (CTAF) L 257.6	121.7 348.6	122.95



DME or RADAR REQUIRED

ELEV 401 | D | TDZE 382



REIL Rwy 18
REIL Rwy 14 L
HIRL Rwy 18-36
HIRL Rwy 14-32 L

318° 5.4 NM from FAF

FAF to MAP 5.4 NM					
Knots	60	90	120	150	180
Min:Sec	5:24	3:36	2:42	2:10	1:48



CATEGORY	A	B	C	D
S-ILS 32 **	582/24 200 (200-½)			
S-LOC 32	1220/24 838 (900-½)	1220/40 838 (900-¾)	1220-1⅞ 838 (900-1⅞)	
C CIRCLING	1220-1¼ 819 (900-1¼)		1220-2½ 819 (900-2½)	1220-2¾ 819 (900-2¾)
FEKRA FIX MINIMUMS				
S-LOC 32	820/24 438 (500-½)		820/40 438 (500-¾)	
C CIRCLING	860-1 459 (500-1)		920-1½ 519 (600-1½)	1040-2 639 (700-2)

SE-4, 10 SEP 2020 to 08 OCT 2020
SE-4, 10 SEP 2020 to 08 OCT 2020