COCOA BEACH, FLORIDA

ILS or LOC/DME RWY 3

LOC I-COF	APCH CRS	Rwy ldg / TDZE / Arpt Elev
109.1	027°	9003 / 6 / 8

AL-38 [USAF]

PATRICK AFB (KCOF)

T * When ALS inop increase RVR to 40 and vis to ¾ mile.
** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CD vis to 1¼ miles.

ALSF-1 (A1)

MISSED APPROACH: Climb to 600, then turn right to intercept the COF R-110 direct ZEVEX, maintain 3000 and hold.

ATIS ★	ORLANDO APP CON	PATRICK TOWER ★	GND CON	CLNC DEL
119.175 273.5	132.65 281.425	133.75 269.375	124.35 335.8	118.4 289.4

*** Circling not authorized W of Rwy 3-21. When Rwy 29 VGSI inop, circling to Rwy 29 NA at night. USAF only: When Rwy 29 VGSI inop, circling to Rwy 29 at night authorized with MAJCOM A3 approval.

506
1046
LOCALIZER 109.1
I-COF
PATRICK
Chan 97 COF
DME available on freq 115.0
124
80
R-110
200
Max holding alt 8000
110°
290°
(IAF)
ZEVEX
COF 12
333
26
241
FIVMA
/RADAR
COF 4.9
475
JAPEK
COF 7.1
207°
027°
278
DME REQUIRED
FIGDA
COF 12
LR-195
COF 12 Arc
MSA COF 25 NM
200°
3000
1600
350°
R-207
525
EMERG SAFE ALT 100 NM 3000

ELEV 8 | TDZE 6
Rwy 29 ldg 3700′
HIRL Rwy 3-21
MIRL 11-29

152
109
21
11
29
4000 × 200
9003 × 200
TWR
166
027° 3.9 NM from FAF
3

ZEVEX R-110 12
FIGDA Intcp Lczr 12
VGSI and descent angles not coincident.
JAPEK 7.1
FIVMA 4.9 /RADAR
3000
3000
027°
2000
1300
2.2
GEPRE 1.5
TACAN
Arc 12
GS 3.00°
TCH 52
1300
3.4
0.5
600
3000
COF R-110

LOC FAF to MAP 3.4 NM					
Knots	60	90	120	150	180
Min:Sec	3:24	2:16	1:42	1:22	1:08

CATEGORY	A	B	C	D
S-ILS 3 *	205/24 200 (200-½)			
S-LOC 3 **	440/24 435 (500-½)		440/40 435 (500-¾)	
CIRCLING ***	480-1 472 (500-1)	500-1 492 (500-1)	500-1½ 492 (500-1½)	560-2 552 (600-2)

SE-3, 08 OCT 2020 to 05 NOV 2020