LOC/DME I-OLV	APP CRS	Rwy Idg	6000
109.3	181°	TDZE	402
Chan 30		Apt Elev	402

ILS or LOC RWY 18
OLIVE BRANCH (OLV)

When local altimeter setting not received, use Memphis Intl altimeter setting and increase all DA 32 feet and all MDA 40 feet, increase S-LOC 18 Cats C and D visibility ⅛ mile and Circling Cats C and D visibility ¼ mile; increase WIMUB fix minimums Circling Cats C and D visibility ¼ mile.

MALSR

MISSED APPROACH: Climb to 1100 then climbing left turn to 2500 on heading 074° and on MEM VORTAC R-102 to ZAMXU INT/MEM 25.7 DME and hold.

ATIS	MEMPHIS APP CON	OLIVE BRANCH TOWER ★	GND CON	CLNC DEL	CLNC DEL	UNICOM
119.925	125.8 338.3	125.275 (CTAF) L	121.2	121.2	121.3 (When twr closed)	122.95

ALTERNATE MISSED APCH FIX

HOLLY SPRINGS
HLI
112.4
Chan 71

112°
292°
R-112

GPS REQUIRED FOR TAA

001°
181°
001°
1 min
4 NM

(IF/IAF)
EFPUB INT
I-OLV 11.9
RADAR

1450

MEMPHIS
117.5 MEM
Chan 122

R-045
2000
181°
(5.9)

NUXAH INT
I-OLV 6
RADAR

R-071
R-091
509±
834
559
861

WIMUB INT
I-OLV 2.5

686
697

LOCALIZER 109.3
I-OLV
Chan 30

MSA HLI 25 NM
2500

MEM R-045 and HLI R-326 may be used to locate EFPUB intersection.

30 NM to EFPUB (NoPT)
2500
EFPUB
091°
271°

091°
271°
EFPUB
2500
30 NM to EFPUB

MEM R-102
102°
282°
R-004
ZAMXU
MEM 25.7

2500 to EFPUB
326° (27.8)

HOLLY SPRINGS
112.4 HLI
Chan 71

ELEV 402
TDZE 402
181° 4.9 NM from FAF
18
36
TWR
6000 X 100
HIRL Rwy 18-36

FAF to MAP 4.9 NM					
Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38

One Minute or 4 NM Holding Pattern
EFPUB INT
I-OLV 11.9
RADAR
NUXAH INT
I-OLV 6
RADAR
1100
2500
hdg 074°
MEM R-102
ZAMXU
*LOC only
2500
001°
181°
2000
WIMUB INT
I-OLV 2.5
I-OLV 1.1
*900 when using Memphis Intl altimeter setting.
GP 3.00°
TCH 51
2000
*860
5.9 NM
3.5 NM
1.4 NM

CATEGORY	A	B	C	D
S-ILS 18	602-½ 200 (200-½)			
S-LOC 18	860-½ 458 (500-½)		860-⅞ 458 (500-⅞)	
C CIRCLING	1060-1 658 (700-1)		1060-1¾ 658 (700-1¾)	1200-2½ 798 (800-2½)
WIMUB FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)				
S-LOC 18	760-½ 358 (400-½)		760-⅝ 358 (400-⅝)	
C CIRCLING	1060-1 658 (700-1)		1060-1¾ 658 (700-1¾)	1200-2½ 798 (800-2½)

SC-4, 08 OCT 2020 to 05 NOV 2020
SC-4, 08 OCT 2020 to 05 NOV 2020