

RADAR INSTRUMENT APPROACH MINIMUMS

BIGGS AAF (KBIF), Fort Bliss, TX Amdt 7A (20198) (USA)

ELEV **3947**

RADAR - 124.15 307.0 **T** **A** NA

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR ¹	22		AB	4460-¾	513	(600-¾)
			CDE	4460-1	513	(600-1)
C CIR ²	22		AB	4460-1	513	(600-1)
			C	4540-1½	593	(600-1½)
			DE	4540-2	593	(600-2)

¹When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1¾ miles.

²CAT DE circling west of Rwy 4-22 NA.

08 OCT 2020 to 05 NOV 2020

08 OCT 2020 to 05 NOV 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

20198

N2

RADAR INSTRUMENT APPROACH MINIMUMS

CORPUS CHRISTI NAS (TRUAX FLD) (KNGP), Corpus Christi, TX

Amdt 1 (20198) (USN)

ELEV 19

RADAR - (E) 6835 124.65 270.8 284.6 337.2 354.8

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR ¹	13R ^{2,7}	3.0°/42/777	ABCDE	113-¾	100	(100-¾)
	18 ⁷	3.0°/39/703	ABCDE	119-½	100	(100-½)
	31L ⁹	3.0°/43/820	ABCDE	118-½	100	(100-½)
	36 ⁹	3.0°/45/831	ABCDE	119-½	100	(100-½)
PAR W/O GS ¹	13R ³		ABCDE	360-¾	347	(400-¾)
	18		ABCDE	340-1⅙	321	(400-1⅙)
	31L		AB	420-1	402	(500-1)
			CDE	420-1⅙	402	(500-1⅙)
PAR W/O GS SIDESTEP ^{1,5}	13L		AB	360-1	341	(400-1)
			C	360-1½	341	(400-1½)
	31R		DE	360-2	401	(400-2)
			AB	420-1	401	(500-1)
ASR	18		AB	400-1	381	(400-1)
			CDE	400-1⅙	381	(400-1⅙)
	13R ^{4,10}		AB	420-¾	407	(500-¾)
			CDE	420-1	407	(500-1)
	13L		AB	420-1	401	(500-1)
			CDE	420-1⅙	401	(500-1⅙)
	4 ¹¹		AB	500-1	483	(500-1)
			CDE	500-1⅙	483	(500-1⅙)
	31L		AB	500-1	482	(500-1)
			CDE	500-1⅙	482	(500-1⅙)
	31R		AB	500-1	481	(500-1)
			CDE	500-1⅙	481	(500-1⅙)
36		AB	500-1	481	(500-1)	
		CDE	500-1⅙	481	(500-1⅙)	
CIR ⁶	ALL RWYS		AB	500-1	481	(500-1)
			C	540-1½	521	(600-1½)
			D	620-2	601	(700-2)
			E	620-2¼	601	(700-2¼)

(CONTINUED ON NEXT PAGE)

08 OCT 2020 to 05 NOV 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

20198

N2

SC-3

RADAR INSTRUMENT APPROACH MINIMUMS

CORPUS CHRISTI NAS (TRUAX FLD) (KNGP) (CON'T) TX

¹No-NOTAM MP: PAR Mon 1300-1700Z++.

²When ALS inop, increase vis CAT ABCDE to ½ mile.

³When ALS inop, increase vis CAT ABCDE to 1 ¼ miles.

⁴When ALS inop increase vis CAT AB to 1 mile, CAT CDE to 1 ½ miles.

⁵Circling from Sidestep NA. Sidestep from PAR W/O GS only; NA prior to 2 miles from thld.

⁶Circling authorized only from ASR and PAR W/O GS. When circling from PAR W/O GS increase vis CAT AB to 1 ½ miles.

⁷CAUTION: TCH (42 feet) is less than the min CAT II Precision TCH (50 feet).

⁸CAUTION: TCH (45 feet) is less than the min CAT II Precision TCH (50 feet).

⁹CAUTION: TCH (43 feet) is less than the min CAT II Precision TCH (50 feet).

¹⁰SDF at 2 NM from thld, 660' min.


¹¹SDF at 3 NM from thld, 980' min.


EL PASO, TX

Amdt 15B, 26MAR20 (20086) (FAA)

ELEV **3962**

EL PASO INTL (ELP)

RADAR-1 124.25 298.85 

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	22		AB	4320/24	371	(400-½)	CDE	4320/40	371	(400-¾)
	26L		ABCDE	4400-¾	438	(500-¾)				
	4		AB	4400/55	483	(500-1¼)	CDE	4400-1¾	483	(500-1¾)
 CIRCLING ALL RWY			A	4420-1	458	(500-1)	B	4440-1	478	(500-1)
			C	4460-1½	498	(500-1½)	D	4680-2¼	718	(800-2¼)
			E	4700-2½	738	(800-2½)				


Circling NA for CATS D and E west of Rwy 4-22.


For inoperative ALS, increase S-4 CAT C/D/E visibility to 1% SM, increase S-22 CAT C/D/E visibility to RVR 5500; increase S-26L CAT E visibility to 1¼ SM.

FORT HOOD/KILLEEN, TX Orig-A, 24MAY18 (18144) (FAA)

ELEV **1015**

ROBERT GRAY AAF (GRK)

RADAR-1 - 120.075 323.15  NA

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	33		AB	1460-¾	465	(500-¾)	CDE	1460-1	465	(500-1)
	15		AB	1520/40	505	(600-¾)	CDE	1520/55	505	(600-1¼)
 CIRCLING ALL RWY			AB	1540-1¼	525	(600-1¼)	C	1560-1½	545	(600-1½)
			D	1620-2	605	(700-2)	E	1740-2½	725	(800-2½)

Circling NA W of Rwy 15-33.

For inoperative ALS, increase ASR S-15 and ASR S-33 CATS C/D/E visibility to 1% mile.

RADAR INSTRUMENT APPROACH MINIMUMS

08 OCT 2020 to 05 NOV 2020

08 OCT 2020 to 05 NOV 2020

RADAR MINS

20198

N4

RADAR INSTRUMENT APPROACH MINIMUMS

FORT HOOD/KILLEEN, TX Orig-A, 24MAY18 (18144) (FAA)

ELEV 1015

ROBERT GRAY AAF (GRK)

RADAR-2 - 120.075 323.15 **▽ ▲** NA

PAR	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
	33	3.00°/53/973	ABCDE	1208-½	213	(200-½)
	15	3.00°/51/1062	ABCDE	1215/24	200	(200-½)

For inoperative ALS, increase PAR S-15 CAT E visibility to RVR 4000 and PAR S-33 CAT E visibility to ¾ SM.
Rwy 15 VGSI and PAR glidepath not coincident (VGSI Angle 3.00/TCH 71).
Rwy 33 VGSI and PAR glidepath not coincident (VGSI Angle 2.77/TCH 52).

KINGSVILLE NAS (KNQI), Kingsville, TX 16JUL20 (20198) (USN)

ELEV 50

RADAR¹ - (E) 128.45X 300.4X 305.2X 310.8X 322.0X 325.2X 358.0X 363.6X 384.4X **▽**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATh/ HAA</u>	<u>CEIL-VIS</u>
PAR ⁶⁷	35R ²	3.0°/32/614	ABCDE	147-¾	100	(100-¾)
	13L	3.0°/34/631	ABCDE	148-½	100	(100-½)
	13R	3.0°/31/610	ABCDE	150-½	100	(100-½)
	17L	3.0°/32/596	ABCDE	148-½	100	(100-½)
	17R	3.0°/34/640	ABCDE	148-½	100	(100-½)
	31L	3.0°/32/583	ABCDE	141-½	100	(100-½)
	31R	3.0°/36/671	ABCDE	137-½	100	(100-½)
PAR W/O GS ⁶⁷	35R ³		ABCDE	340-¾	293	(300-¾)
	17L		ABCDE	320-1¼	272	(300-1¼)
	17R		ABCDE	320-1¼	272	(300-1¼)
	31L		ABCDE	320-1¼	279	(300-1¼)
	31R		ABCDE	320-1¼	283	(300-1¼)
	13L		ABCDE	460-1¼	412	(500-1¼)
ASR	13R		ABCDE	460-1¼	410	(500-1¼)
	35R ⁴		AB	420-½	373	(400-½)
			CDE	420-¾	373	(400-¾)
	17L		ABCDE	340-1	292	(300-1)
	17R		ABCDE	400-1	352	(400-1)
	31L		ABCDE	360-1	319	(400-1)
	31R		ABCDE	360-1	323	(400-1)
	35L		ABCDE	420-1	372	(400-1)
	13L		AB	500-1	452	(500-1)
			CDE	500-1¾	452	(500-1¾)
CIR ⁵	13R		AB	460-1	410	(500-1)
			CDE	460-1½	410	(500-1½)
			C	780-2	730	(800-2)
			D	780-2¼	730	(800-2¼)
	ALL RWYS		E	780-2½	730	(800-2½)

(CONTINUED ON NEXT PAGE)

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

20198

N4

SC-3

08 OCT 2020 to 05 NOV 2020

RADAR INSTRUMENT APPROACH MINIMUMS

KINGSVILLE NAS (KNQI) (CON'T) TX

- ¹Use landing/taxi lights when conducting apch during VMC.
- ²When ALS inop, increase vis CAT ABCDE to ½ mile.
- ³When ALS inop, increase vis CAT ABCDE to 1¼ mile.
- ⁴When ALS inop, increase vis CAT ABCDE to 1 mile.
- ⁵Circling authorized only from PAR W/O GS and ASR.
- ⁶No NOTAM MP: PAR 1300-1700Z++Mon. Maint conducted next bus day if clsd on Mon.
- ⁷PAR sked for maint ev Wed, wx permitting.

MIDLAND, TX

Amdt 7, 22JUN17 (17173) (FAA)

ELEV 2872

MIDLAND INTL AIR AND SPACE PORT (MAF)

RADAR-1 124.6 290.4 **▽ ▲**

ASR	RWY	GP/TCH/RPI	CAT	DA/	HAT/	CEIL-VIS	CAT	DA/	HAT/	CEIL-VIS
				MDA-VIS	HAA			MDA-VIS	HAA	
	28		AB	3280-¾	425	(500-¾)	CDE	3280-1	425	(500-1)
	34L		AB	3320-1	462	(500-1)	CDE	3320-1½	462	(500-1½)
	4		AB	3360-1	509	(500-1)	CDE	3360-1½	509	(500-1½)
	16R		AB	3400-1	528	(600-1)	CDE	3400-1½	528	(600-1½)
	10		AB	3480/24	611	(700-½)	CDE	3480-1½	611	(700-1½)
	22		AB	3540-1	685	(700-1)	CDE	3540-2	685	(700-2)
C CIRCLING	ALL RWY		AB	3540-1	668	(700-1)	C	3540-1¾	668	(700-1¾)
			D	3540-2	668	(700-2)	E	3580-2½	708	(800-2½)

- For inoperative ALS, increase ASR-10 Cat C/D/E visibility to 1¼ mile.
- For inoperative ALS, increase ALS-28 Cat D/E visibility to 1¼ mile.
- Night Landing: Rwy 16L NA.
- When control tower closed, ASR NA.

SAN ANGELO, TX

Amdt 1B, 28FEB19 (19059) (FAA)

ELEV 1919

SAN ANGELO RGNL/MATHIS FIELD (SJT)

RADAR-1 125.35 354.1 **▽ ▲**

ASR	RWY	GP/TCH/RPI	CAT	DA/	HAT/	CEIL-VIS	CAT	DA/	HAT/	CEIL-VIS
				MDA-VIS	HAA			MDA-VIS	HAA	
	36		AB	2460-1	541	(600-1)	CDE	2460-1½	541	(600-1½)
	18		AB	2500-1	592	(600-1)	CDE	2500-1¼	592	(600-1¼)
C CIRCLING	ALL RWY		AB	2500-1	641	(700-1)	C	2500-1¼	641	(700-1¼)
			D	2700-2½	781	(800-2½)	E	2700-2¼	781	(800-2¼)

- Circling NA for Cat E west of Rwy 18-36.
- When control tower closed, ASR NA.
- Rwy 36 helicopter visibility reduction below ¾ SM not authorized.

08 OCT 2020 to 05 NOV 2020

08 OCT 2020 to 05 NOV 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

20198

N6

RADAR INSTRUMENT APPROACH MINIMUMS

WACO, TX

Amdt 1A, 11FEB10 (10042) (FAA)

ELEV 592

MC GREGOR EXECUTIVE (PWG)

RADAR-1 127.65 352.0 **▼**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	17		AB	1020-1	430	(500-1)	C	1020-1¼	430	(500-1¼)
			D	NA						
CIRCLING	ALL RWY		A	1040-1	448	(500-1)	B	1060-1	468	(500-1)
			C	1060-1½	468	(500-1½)	D	NA		

WACO, TX

Amdt 4, 11FEB10 (10042) (FAA)

ELEV 470

TSTC WACO (CNW)

RADAR-1 127.65 227.125 **▼ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	17L		AB	1080-½	611	(700-½)	C	1080-1¼	611	(700-1¼)
			D	1080-1½	611	(700-1½)				
CIRCLING	ALL RWY		AB	1080-1	610	(700-1)	C	1080-1¼	610	(700-1¼)
			D	1080-2	610	(700-2)				

When Waco Regional approach control closed, ASR not authorized.

WACO, TX

Amdt 4, 23SEP10 (14317) (FAA)

ELEV 516

WACO RGNL (ACT)

RADAR-1 127.65 227.125 **▼**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	19		ABC	880/24	376	(400-½)	D	880/50	376	(400-1)
	1		ABC	860-1	351	(400-1)	D	860-1¼	351	(400-1¼)
	14		AB	920-1	407	(500-1)	CD	920-1¼	407	(500-1¼)
	32		AB	1020-1	504	(600-1)	CD	1020-1½	504	(600-1½)
CIRCLING	ALL RWY		AB	1020-1	504	(600-1)	C	1020-1½	504	(600-1½)
			D	1080-2	564	(600-2)				

For inoperative MALSR increase S-19 CAT D visibility to RVR 6000.

When control tower closed, ASR NA.

08 OCT 2020 to 05 NOV 2020

08 OCT 2020 to 05 NOV 2020

SC-3

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

20198

N6