

RADAR MINS

20254

N1

RADAR INSTRUMENT APPROACH MINIMUMS

ALBEMARLE, NC
STANLY COUNTY (VUJ)
 RADAR-1 128.325 307.8 

Orig, 22JUN17 (19059) (FAA)

ELEV 609

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR	22L	3.0°/40/767	ABCD	784-¾	200	(200-¾)

Procedure NA when control tower closed.

BEAUFORT, SC
BEAUFORT COUNTY (ARW)
 RADAR-1 125.125 292.125  NA

Amdt 3A, 10MAY07 (11013) (FAA)

ELEV 10

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	25		ABC	440-1¼	430	(500-1¼)				
CIRCLING	ALL RWY		AB	500-1¼	490	(500-1¼)	C	500-1½	490	(500-1½)

Use Beaufort MCAS/Merritt Field altimeter setting.
 When Beaufort Class D not in effect, procedure NA.

08 OCT 2020 to 05 NOV 2020

08 OCT 2020 to 05 NOV 2020

SE-2

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

20254

N1

RADAR INSTRUMENT APPROACH MINIMUMS

BEAUFORT MCAS (MERRITT FLD) (KNBC), Beaufort, SC

Amdt 5 18JUN20 (20254) (USN)

ELEV 37

RADAR - (E) 123.7x 298.875x 317.775x 323.275x 338.35x 372.0x 379.275x **▽**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR ¹	23 ²	3.0°/44/821	ABCDE	116 -¼	100	(100-¼)
	5 ²	3.0°/38/779	ABCDE	137 -¼	100	(100-¼)
	14	3.0°/41/780	ABCDE	233 -¾	200	(200-¾)
	32 ⁸	3.0°/40/722	ABCDE	308 -⅞	283	(300-⅞)
PAR W/O GS ¹	23 ^{5 6}		ABCDE	320 -½	304	(300-½)
	14 ⁶		AB	420 -1	387	(400-1)
			CDE	420 -1½	387	(400-1½)
			AB	440 -¾	403	(500-¾)
	5 ^{3 7}		CDE	440 -1	403	(500-1)
			AB	440 -1	415	(500-1)
	32 ⁶		AB	440 -1	415	(500-1½)
			CDE	440 -1½	415	(500-1½)
ASR ^{1 6}	23 ³		AB	360 -½	344	(400-½)
			CDE	360 -⅝	344	(400-⅝)
	14		AB	420 -1	387	(400-1)
			CDE	420 -1½	387	(400-1½)
	5 ⁴		AB	460 -¾	423	(500-¾)
			CDE	460 -1	423	(500-1)
	32		AB	500 -1	475	(500-1)
			CDE	500 -1½	475	(500-1½)
CIR	5, 14, 23, 32		AB	500 -1	463	(500-1)
			C	600 -1½	563	(600-1½)
			D	600 -2	563	(600-2)
			E	740 -2½	703	(800-2½)

¹No-NOTAM MP 1200-2000Z++ Sat.

²When ALS inop, increase vis CAT ABCDE to ½ mile.

³When ALS inop, increase vis CAT ABCDE to 1 mile.

⁴When ALS inop, increase vis CAT AB to 1 mile, CAT CDE to 1¼ miles.

⁵When ALS inop, increase vis CAT ABCDE to 1 mile.

⁶VDA and VGSI not coincident.

⁷When ALS inop, increase vis CAT AB to 1 mile, CAT CDE to 1½ miles.

⁸WCH for Group 4 is 16ft.

CODED LOST COMMUNICATIONS

SCARLET

TACAN equipped aircraft: If no transmissions are received for one minute in the pattern or 5/15 seconds on final approach, attempt contact with Beaufort Tower on 342.875/119.05 and proceed VFR. If unable, climb and maintain two thousand six hundred, proceed direct COSAW, execute TACAN Rwy 23 approach.

GOLD

RNAV/GPS equipped aircraft: If no transmissions are received for one minute in the pattern or 5/15 seconds on final approach, attempt contact with Beaufort Tower on 342.875/119.05 and proceed VFR. If unable, climb and maintain two thousand eight hundred, proceed direct HOWEL and execute RNAV/GPS Rwy 23 approach.

08 OCT 2020 to 05 NOV 2020

08 OCT 2020 to 05 NOV 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

CHERRY POINT MCAS (CUNNINGHAM FLD) (KNKT), Cherry Point, NC

Amdt 3 10SEP20 (20254) (USN)

ELEV 29

RADAR - (E) 118.35x 120.15x 275.6x 299.6x 305.2x 314.8x 320.4x 337.2x 348.0x **T**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR	32L ¹ ₃	3.0°/57/1048	ABCDE	126 -¼	100	(100-¼)
	14L ³	3.0°/55/1056	ABCDE	126 -½	100	(100-½)
	5R ³	3.0°/56/1049	ABCDE	127 -½	100	(100-½)
	23R ³	3.0°/57/1076	ABCDE	123 -½	100	(100-½)
ASR	23R ⁴		AB	400 -½	377	(400-½)
			CDE	400 -¾	377	(400-¾)
	32L ²		AB	400 -½	394	(400-½)
			CDE	420 -¾	394	(400-¾)
	5R		AB	500 -1	473	(500-1)
			CDE	500 -1¾	473	(500-1¾)
14L		AB	500 -1	474	(500-1)	
		CDE	500 -1¾	474	(500-1¾)	
CIR	ALL RWYS		AB	580 -1	551	(600-1)
			C	600 -1½	571	(600-1½)
			D	600 -2	571	(600-2)
			E	700 -2½	671	(700-2½)

¹When ALS inop, increase vis CAT ABCDE to ½ mile.

²When ALS inop, increase vis CAT AB to 1 mile, CAT CDE to 1½ miles.

³CAUTION: PAR RPI and PAPI RRP are not coincident.

⁴When ALS inop, increase vis CAT ABCDE to 1 mile.

08 OCT 2020 to 05 NOV 2020

08 OCT 2020 to 05 NOV 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

NEW RIVER MCAS (KNCA), (MC CUTCHEON FLD) NC (Jacksonville) (Amdt 1, 19059 USN)

RADAR - (U) 118.575 132.2 279.575 289.4 308.4 346.325 350.225 353.875 **▽**

ELEV 26

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATh/ HAA</u>	<u>CEIL-VIS</u>
PAR	1 ¹	3.0°/45/872	ABCD	124-¾	100	(100-¾)
	5 ⁵	3.0°/36/656	ABCD	126-½	100	(100-½)
	19 ³	3.0°/40/757	ABCD	123-½	100	(100-½)
	23 ⁴	3.0°/37/664	ABCD	274-⅙	250	(300-⅙)
PAR W/O GS	1 ²		ABCD	340-¾	316	(400-¾)
	5		ABCD	400-1	374	(400-1)
	19		ABCD	400-1	377	(400-1)
	23		AB	440-1	416	(500-1)
			CD	440-1⅙	416	(500-1⅙)
ASR	5		ABCD	400-1	374	(400-1)
	23		ABCD	380-1	356	(400-1)
	19		AB	440-1	417	(500-1)
			CD	440-1⅙	417	(500-1⅙)
CIR	ALL RWY		AB	500-1	474	(500-1)
			C	500-1½	474	(500-1½)
			D	580-2	554	(600-2)

¹When ALS inop, increase vis to ½ mile.

²When ALS inop, increase vis CAT ABCD to 1 mile. The difference between the VGSI TCH (45 ft) and the procedure TCH (49 ft) is greater than 3 ft.

³CAUTION: WCH for Group 4: 18 ft is less than the min WCH 20 ft.

⁴CAUTION: WCH for Group 3: 16 ft and Group 4: 11 ft is less than the min WCH 20 ft.

⁵CAUTION: WCH for Group 3: 15 ft and Group 4: 10 ft is less than the min WCH 20 ft.

08 OCT 2020 to 05 NOV 2020

08 OCT 2020 to 05 NOV 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

20254

N5

RADAR INSTRUMENT APPROACH MINIMUMS

SIMMONS AAF (KFBG), NC (Fort Bragg) (1-Amdt 12, 2-Orig 11097 USA)

ELEV 244

RADAR¹ - (E) 120.8 124.2 257.65 284.675 **▼**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
RADAR-1						
PAR	27	3.0°/36/628	ABC	428 -¾	200	(200-¾)
			D	NA	NA	NA
PAR W/O GS	27		AB	640 -1	412	(500-1)
			C	640 -1¼	412	(500-1¼)
			D	NA	NA	NA
CIR			AB	780 -1	536	(600-1)
			C	780 -1½	536	(600-1½)
			D	NA	NA	NA
RADAR-2						
PAR	9	3.9°/33/487	COPTER	491 -½	250	(300-½)

¹Opr 1200-0400Z++ Mon-Fri, clsd hol. No-NOTAM preventive maint 1800-1900Z++ Fri.

WILMINGTON, NC

Amdt 7A, 17AUG17 (17229) (FAA)

ELEV 32

WILMINGTON INTL (ILM)

RADAR-1 118.25 135.75 284.65 317.425 **▼ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	24		AB	500 /24	474	(500-½)	CD	500 /50	474	(500-1)
	35		AB	500 /40	469	(500-¾)	CD	500 /50	469	(500-1)
	17		AB	500 -1	468	(500-1)	CD	500 -1%	468	(500-1%)
	6		AB	540 /55	512	(600-1¼)	CD	540 -1%	512	(600-1%)
C CIRCLING	ALL RWY		AB	560 -1	528	(600-1)	C	720 -2	688	(700-2)
			D	920 -3	888	(900-3)				

When control tower closed, ASR NA.

Rwy 17 helicopter visibility reduction below ¾ SM not authorized.

For inop ALS, increase S-24 Cat C/D visibility to 1% SM, and S-35 Cats A/B visibility to RVR 5500, and Cat C/D to 1% SM.

08 OCT 2020 to 05 NOV 2020

08 OCT 2020 to 05 NOV 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

20254

N5

SE-2