

RADAR INSTRUMENT APPROACH MINIMUMS

FALLON NAS (KNFL), (VAN VOORHIS FLD), NV (Amdt 3, 19311 USN)

ELEV 3935

RADAR¹ - (E) 120.85x 121.875x 257.65x 277.4x 308.4x 346.4x 360.2x **▽**

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR	7	3.0°/35/661	ABCDE	4129 -¾	200	(200-¾)
	13L	3.0°/47/892	ABCDE	4135 -¾	200	(200-¾)
	13R	3.0°/50/959	ABCDE	4135 -¾	200	(200-¾)
	31L ²	3.5°/57/928	ABCDE	4127 -¾	200	(200-¾)
	31R	3.5°/57/929	ABCDE	4128 -¾	200	(200-¾)
ASR	31L ³		ABCDE	4220 -1	293	(300-1)
	31R ⁴		ABCDE	4220 -1	292	(300-1)
	13L ⁶		AB	4320 -1	385	(400-1)
			CDE	4320 -1½	385	(400-1½)
	13R ⁵		AB	4320 -1	385	(400-1)
			CDE	4320 -1½	385	(400-1½)
	7		AB	4340 -1	411	(500-1)
		CDE	4340 -1½	411	(500-1½)	
CIR	ALL RWY		AB	4400 -1	465	(500-1)
			C	4700 -2¼	765	(800-2¼)
			D	4920 -3	985	(1000-3)
			E	4960 -3	1025	(1100-3)

CAUTION: ATC Missed Approach Minimum Climb Rate to 7400

PAR/ASR	Rwy	Knots	60	120	180	240	300	360
	7	FPM	260	520	780	1040	1300	1560
	13L/R	FPM	260	520	780	1040	1300	1560
	31L/R	FPM	270	540	810	1080	1350	1620

¹No-NOTAM MP sked: PAR-2200-0000Z++ Thu, ASR-1500-1700Z++ Wed, when ceil-vis 3000-5 and above.

²PAR and PAPI not coincident.

³Step Down Fix 3 NM 4980'.

⁴Step Down Fix 3 NM 4940'.

⁵Step Down Fix 2 NM 4600'.

⁶Step Down Fix 3 NM 4960'.

08 OCT 2020 to 05 NOV 2020

08 OCT 2020 to 05 NOV 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

19339

N2


RADAR INSTRUMENT APPROACH MINIMUMS

FORT HUACHUCA SIERRA VISTA, AZ

Orig-B, 10OCT19 (18283) (FAA)

ELEV 4719

SIERRA VISTA MUNI-LIBBY AAF (FHU)

RADAR-1 127.05 254.35  NA

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
PAR	26	3.00°/50/950	ABCDE	4799-¾	200	(100-¾)
	8	3.00°/41/782	ABCDE	4919-¾	200	(200-¾)
PAR W/O GS	26		AB	5080-1	481	(400-1)
			CDE	5080-1¾	481	(400-1¾)
	8		AB	5100-1	381	(400-1)
			CDE	5100-1½	381	(400-1½)
CIRCLING	ALL RWY		A	5080-1	381	(400-1)
			B	5180-1	461	(500-1)
			C	5180-1½	461	(500-1½)
			D	5280-2	561	(600-2)
			E	5340-2¼	621	(700-2¼)


Circling NA south of Rwy 8-30.
Procedure NA when control tower is closed.

FORT HUACHUCA SIERRA VISTA, AZ

Orig-B, 10OCT19 (19283) (FAA)

ELEV 4719

SIERRA VISTA MUNI-LIBBY AAF (FHU)

RADAR-2 127.05 254.35  NA

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	26		AB	5180-1	581	(500-1)
			CDE	5180-1¼	581	(500-1¼)
			8	AB	5380-1	661
CDE	5380-1½	661		(700-1½)		
CIRCLING	26		AB	5180-1	461	(500-1)
			C	5180-1¼	461	(500-1¼)
			D	5280-2	561	(600-2)
			E	5340-2¼	621	(700-2¼)
			8	AB	5380-1	661
	C			5380-1½	661	(700-1½)
	D			5380-2	661	(700-2)
	E			5380-2¼	661	(700-2¼)

Circling NA south of Rwy 8-30.
ASR NA when tower is closed.

08 OCT 2020 to 05 NOV 2020

08 OCT 2020 to 05 NOV 2020

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

19339

N2

SW-4

RADAR INSTRUMENT APPROACH MINIMUMS

YUMA MCAS/YUMA INTL (KNYL), AZ (19171 USN)

ELEV 213

RADAR - (E) 120.9x 124.15x 125.55x 125.95x 254.0x 270.8x 278.7x 286.0x 301.2x 305.2x



	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR	21R ¹	3.0°/54/1073	ABCDE	393-½	200	(200-½)
	3L	3.0°/54/1021	ABCDE	395-¾	200	(200-¾)
PAR W/O GS	3L		ABCDE	560-1	365	(400-1)
	21R ²		AB	600-½	407	(400-½)
			CDE	600-¾	407	(400-¾)
ASR	3L		ABCDE	560-1	365	(400-1)
	3R		AB	600-1	412	(400-1)
			CDE	600-1½	412	(400-1½)
	21L		AB	640-1	432	(500-1)
			CDE	640-1¼	432	(500-1¼)
	21R ³		AB	640-½	447	(500-½)
			CDE	640-⅔	447	(500-⅔)
CIRCLING	ALL RWY		A	680-1	467	(500-1)
			B	700-1	487	(500-1)
			C	800-1½	587	(600-1½)
			DE	800-2	587	(600-2)

¹When ALS inop, increase CAT ABCDE vis to ¾ mile.

²When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1½ miles.

³When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1½ miles.

08 OCT 2020 to 05 NOV 2020

08 OCT 2020 to 05 NOV 2020

RADAR INSTRUMENT APPROACH MINIMUMS