

WAAS CH <b>87004</b>	APP CRS <b>194°</b>	Rwy Idg TDZE Apt Elev	<b>6115</b> <b>1065</b> <b>1071</b>
-------------------------	------------------------	-----------------------------	---

# RNAV (GPS) RWY 19




GLENDALE MUNI (GEU)

RNP APCH.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 47°C.  
 ▲ Rwy 19 helicopter visibility reduction below 3/4 SM NA. VDP and Baro-VNAV NA when using Phoenix Sky Harbor Inlt altimeter setting. When local altimeter setting not received, use Phoenix Sky Harbor Inlt altimeter setting: increase LPV DA to 1384 feet; increase LNAV/VNAV DA to 1617 feet and all Cats visibility 1/4 SM; increase all MDA 60 feet and LNAV Cat C and D visibility 1/4 SM.

MISSED APPROACH: Climb to 5000 direct AGERE then climb to 8000 on track 132° to POTER and hold.

ATIS <b>119.425</b>	LUKE APP CON* <b>118.15 363.125</b>	GLENDALE TOWER* <b>121.0 (CTAF)</b>	GND CON <b>118.0</b>	UNICOM <b>122.95</b>
------------------------	--	--	-------------------------	-------------------------



	1.1 NM	0.7	3.7 NM	6 NM
CATEGORY	A	B	C	D
LPV DA	1339-1		274 (300-1)	
LNAV/VNAV DA	1572-1 3/4		507 (600-1 3/4)	
LNAV MDA	1540-1	475 (500-1)	1540-1 3/8 475 (500-1 3/8)	1540-1 1/2 475 (500-1 1/2)

SW-4, 28 JAN 2021 to 25 FEB 2021

SW-4, 28 JAN 2021 to 25 FEB 2021