

WAAS CH 78437 W35B	APP CRS 355°	Rwy ldg TDZE Apt Elev	5001 1275 1300
--	------------------------	-----------------------------	---



RNAV (GPS) RWY 35L

WILEY POST (PWA)


ASR DME/DME RNP-0.3 NA. VDP NA when using Will Rogers World altimeter setting. When local altimeter setting not received, use Will Rogers World altimeter setting and increase all MDA 40 feet; increase LP Cat C/D visibility 1/8 mile and Circling Cat C 1/4 mile.

MISSED APPROACH: Climb to 1700 then climbing left turn to 3400 direct IFI VORTAC and hold.

ATIS 128.725	OKE CITY APP CON 124.6 266.8	WILEY POST TOWER ★ 126.9(CTAF) 306.9	GND CON 121.7	UNICOM 122.95
------------------------	--	--	-------------------------	-------------------------



ELEV 1300	D	TDZE 1275
-----------	----------	-----------



CATEGORY	LP	MDA	WIGOK		YOCU		4 NM Holding Pattern
			A	B	C	D	
LN	AV	DA	WIGOK		YOCU		4 NM Holding Pattern
			A	B	C	D	
CIRCLING	LP	MDA	WIGOK		YOCU		4 NM Holding Pattern
			A	B	C	D	

SC-1, 25 MAR 2021 to 22 APR 2021

SC-1, 25 MAR 2021 to 22 APR 2021