COPTER ILS or LOC RWY 30

GARY/CHICAGO INTL (GYY)

LOC I-GYY	APP CRS	Rwy Idg	7959
108.75	306°	TDZE	591
Chan 24 (Y)		Apt Elev	597

When local altimeter setting not recieved, use Chicago Midway Intl altimeter setting and increase all DA 46 feet and all MDA 60 feet. VDP NA with Chicago Midway Intl altimeter setting.

MALSR

MISSED APPROACH: Climb to 1500 then climbing left turn to 2300 direct CGT VORTAC and hold.

ATIS	CHICAGO APP CON	GARY TOWER ★	GND CON
134.575	133.1 285.6	125.6 (CTAF) L	121.9

DME or RADAR REQUIRED

LOCALIZER 108.75
I-GYY
Chan 24 (Y)

917 942 942 1111 761 791 923 1006 737 1090 1090 1103

RONOY
I-GYY 3.5
(IAF)
WASTU INT
I-GYY 5.7
RADAR

306°
081°
261°
(CFCFJ)
126°

CHICAGO HEIGHTS
114.2 CGT
Chan 89

2300
069°
(11.7)
R-069
156°
336°
R-156

MSA CGT 25 NM
3400
090° 270°
2800

1731

ALTERNATE
MISSED APCH FIX
R-001
001° 181°
PEOTONE
EON
113.2
Chan 79

ELEV 597 D TDZE 591

640 627 20 8859 X 150 3604 X 100 672 TWR 662 2 12 30

306° 4.3 NM from FAF

1500 2300 CGT

#1300 when using Chicago Midway Intl altimeter setting.
*LOC only

WASTU INT
I-GYY 5.7
RADAR

Remain within 5 NM

RONOY
I-GYY 3.5

2000
126°
306°
2300

*I-GYY
2.6

*1240#
2000

GS 3.00°
HCH 57

1.1 NM 0.9 NM 2.3 NM

REIL Rwys 2, 12 and 20 L
HIRL Rwy 12-30 L
MIRL Rwy 2-20 L

FAF to MAP 4.3 NM

Knots	45	60	75	90	105
Min:Sec	5:44	4:18	3:26	2:52	2:27

CATEGORY	COPTER
S-ILS 30	791-¼ 200 (200-¼)
S-LOC 30	1240-¼ 649 (700-¼)
RONOY FIX MINIMUMS	
S-LOC 30	1000-¼ 409 (500-¼)

EC-2, 20 MAY 2021 to 17 JUN 2021
EC-2, 20 MAY 2021 to 17 JUN 2021