ILS Y or LOC Y RWY 28

STATESVILLE RGNL (SVH)

LOC/DME I-SVH	APP CRS	Rwy Idg	5456
111.75	285°	TDZE	967
Chan 54 (Y)		Apt Elev	968

T A When local altimeter setting not received, use Lincolnton altimeter setting and increase ILS DA to 1219 and all MDA 60 feet; increase S-LOC 28 Cats C/D visibility ⅛ mile and Circling Cat C visibility ¼ mile. VDP NA when using Lincolnton altimeter setting. For inop MALSR when using Lincolnton altimeter setting, increase S-ILS 28 all Cats visibility to ⅞ mile and S-LOC 28 Cats C/D visibility to 1 mile. DME required.

MALSR

MISSED APPROACH: Climb to 1700 then climbing left turn to 3400 on heading 105° and on CLT VOR/DME R-025 to PEGTE INT/I-SVH 13.2 DME and hold.

AWOS-3	ATLANTA CENTER	UNICOM
119.225	125.15 263.0	123.075 (CTAF) L

ALTERNATE MISSED APCH FIX

064° 244° R-064

BARRETTS MOUNTAIN
BZM
110.8
Chan 45



ELEV 968 D TDZE 967



1700	3400 hdg 105°	CLT R-025	PEGTE △

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 50).



CATEGORY	A	B	C	D
S-ILS 28	1167-½ 200 (200-½)			
S-LOC 28	1280-½ 313 (400-½)			
C CIRCLING	1420-1 452 (500-1)	1540-1 572 (600-1)	1540-1½ 572 (600-1½)	1560-2 592 (600-2)

REIL Rwy 10 L
HIRL Rwy 10-28 L

SE-2, 17 JUN 2021 to 15 JUL 2021
SE-2, 17 JUN 2021 to 15 JUL 2021