ILS or LOC RWY 31

TOPEKA RGNL (FOE)

LOC/DME I-FOE	APP CRS	Rwy Idg 12803
110.1	312°	TDZE 1037
Chan 38		Apt Elev 1078

RADAR required for Cat E for Procedure Entry.

For inop ALS, increase S-ILS Cat E visibility to RVR 4000 and S-LOC Cat E visibility to 1¼ SM.

RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 1900 then climbing left turn to 3700 on heading 275° and on TOP VORTAC R-231 to DIETS INT and hold.

ATIS	KANSAS CITY CENTER	FORBES TOWER*	GND CON	UNICOM
128.25	123.8 343.7	120.8 (CTAF) L 340.2	118.425 275.8	122.95



ELEV 1078 D TDZ 1037



REIL Rwys 3, 13 and 21

MIRL Rwy 3-21 L

HIRL Rwy 13-31 L

312° 4.7 NM from FAF

FAF to MAP 4.7 NM

Knots	60	90	120	150	180
Min:Sec	4:42	3:08	2:21	1:53	1:34



CATEGORY	A	B	C	D	E
S-ILS 31 #	1237/24 200 (200-½)				
S-LOC 31	1460/24 423 (400-½)		1460/40 423 (400-¾)		
C CIRCLING	1520-1 442 (500-1)	1580-1 502 (600-1)	1580-1½ 502 (600-1½)	1700-2 622 (700-2)	1720-2¼ 642 (700-2¼)

NC-2, 09 SEP 2021 to 07 OCT 2021
NC-2, 09 SEP 2021 to 07 OCT 2021