CAMP MACKALL, NORTH CAROLINA

RNAV (GPS) RWY 12

WAAS CH 92382 W12A	APCH CRS 118°	Rwy ldg 4794 TDZE 374 Arpt Elev 376

AL-6315 (USA)

MACKALL AAF (KHFF)

* When tower closed, increase vis to 1 mile.
** Circling NA to RWYs 4,16,22, and 34.

MISSED APPROACH: Climb to 2100 direct HITIT and hold.

D-ATIS	FAYETTEVILLE APP CON/DEP CON	TOWER★	GND CON
141.4	127.8 343.725	121.0 (CTAF) 254.4	128.35 251.05

For uncompensated BARO-VNAV systems, LNAV/VNAV NA below -15° or above 54°C.

Rwy 12 helicopter visibility reduction below 3/4 mile NA.

BARO-VNAV NA when using Simmons AAF altimeter setting.

RNP APCH

When local altimeter setting not received, use Simmons AAF altimeter setting.

VDA NA with Simmons AAF altimeter setting.

Additional restrictions are in effect when restricted areas are active.

762 A531 (IAF) ITGUY 2400 208° 30NM to ITGUY 2400 ITGUY 298° 2400 NoPT 208° (8) (IAF/IF) AAMMO 907 118° 230K 298° 2100 118° (8) (FAF) DAZED FIGHT 559 467 RW12 4 NM 118° 230K 298° HITIT HOLD 2100 R5311B R5311C R5311A 2900 208° 30NM to AAMMO 30NM to AAMMO (NoPT) 2400 AAMMO 4 NM HOLD 6000 2400 028° 2400 NoPT 028° (8) JOGTU 298° 2400 (IAF) JOGTU 2400 028° 30NM to JOGTU

2100 HITIT

AAMMO 298° 6000 2400 118° 2400 118° DAZED 2100 FIGHT 1440 1.2 NM to RW12 RW12 GP 3.00° TCH 55 2 NM 3.2 NM

ELEV 376 TDZE 374

118° to RW12 4996 x 100 0.5% DOWN 4790 x 100 0.3% DOWN 4794 x 100 0.9% DOWN 16 22 12 4 34 30

CATEGORY	A	B	C	D
LPV DA*	575-¾ 200 (200-¾)			
LNAV/VNAV DA	851-1⅜ 476 (500-1⅜)			
LNAV MDA	820-1 445 (500-1)		820-1⅜ 445 (500-1⅜)	
C CIRCLING**	860-1 484 (500-1)	880-1 504 (600-1)	980-1¾ 604 (700-1¾)	1020-2 644 (700-2)
SIMMONS AAF ALTIMETER SETTING MINIMUMS				
LPV DA*	659-⅞ 284 (300-⅞)			
LNAV/VNAV DA	935-1⅝ 560 (600-1⅝)			
LNAV MDA	920-1 545 (600-1)		920-1⅝ 545 (600-1⅝)	
C CIRCLING**	960-1 584 (600-1)		1060-2 684 (700-2)	1100-2¼ 724 (800-2¼)

HIRL Rwys 4-22, 12-30

SE-2, 04 NOV 2021 to 02 DEC 2021

SE-2, 04 NOV 2021 to 02 DEC 2021