CLOVIS, NEW MEXICO

TACAN RWY 22

TACAN CVS Chan 53	APCH CRS 212°	Rwy ldg 10,003 TDZE 4295 Arpt Elev 4295

AL-512 [USAF]

CANNON AFB (KCVS)

* When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, increase CAT CDE vis to 1¾ miles.

ALSF-1

† MISSED APPROACH: Climb to 6000 out CVS TACAN R-220 to 6 DME (JEBES) then climbing left turn to 7000 intercept CVS R-193 to 12 DME (CLINK) and hold.

ATIS	CANNON APP CON	CANNON TOWER	GND CON	CLNC DEL
119.1 269.9	118.425 352.1	120.4 270.25	121.9 275.8	120.2 293.225

† Missed approach requires use of RNAV or ATC RADAR monitoring.

5159 4959 CVS 17 Max holding alt 10,000 Min holding alt 7000 003° 265K 183° 4857 4798 6000 CVS 12 Arc LR-022 R-032 (IAF) HEDOB 7000 CVS 12 R-003 (IF) BOJAY CVS 12 212° 4556 JARPI CVS 6 4443 4634 4529 4525 4305 4662 JEBES CVS 6 CANNON Chan 53 CVS 4341 R-220 R-193 CLINK CVS 12 Max holding alt 10,000 Min holding alt 7000 013° 265K 193° CVS 17 4751

EMERG SAFE ALT 100 NM 9000

MSA CVS 25 NM 6600

6000 CVS R-220	JEBES CVS 6	7000	CLINK CVS R-193 12

VGSI and descent angles not coincident.

TACAN ZORUB 1.2 2.9 JARPI 6 212° 5700 BOJAY R-032 12 6000 Arc 12 HEDOB R-003 12 7000 2.67° TCH 33 4.8 NM

ELEV 4295 TDZE 4295

212° 4.8NM from FAF

4433 TWR 4437 22 13 4 31 10,003 x 150 8196 x 150 0.3% UP

CATEGORY	A	B	C	D	E
S-22 *	4900/24 605 (700-½)		4900-1⅜ 605 (700-1⅜)		
C CIRCLING	4900-1 605 (700-1)		4900-1¾ 605 (700-1¾)	5000-2¼ 705 (800-2¼)	5020-2½ 725 (800-2½)

REIL all Rwy
HIRL all Rwy

SW-1, 02 DEC 2021 to 30 DEC 2021