


LOC I-TVR 109.7	APP CRS 357°	Rwy Idg 5002 TDZE 86 Apt Elev 86
---------------------------	------------------------	---


ILS or LOC RWY 36

VICKSBURG TALLULAH RGNL (TVR)

NA ADF required. When local altimeter setting not received, use Vicksburg Muni, MS altimeter setting and increase S-ILS 36 DA to 309 feet; increase all MDA 40 feet and visibility Cats C and D ¼ mile.


SSALR  MISSED APPROACH: Climb to 1000 then climbing left turn to 2100 direct TKH NDB and hold.

ASOS 118.525	MEMPHIS CENTER 132.5 259.1	UNICOM 123.0 (CTAF) 0
------------------------	--------------------------------------	---------------------------------






ADF REQUIRED

ELEV 86	D	TDZE 86
---------	----------	---------



CATEGORY	A	B	C	D
S-ILS 36	286-½		200 (200-½)	
S-LOC 36	540-½	454 (500-½)	540-⅞	454 (500-⅞)
C CIRCLING	540-1	454 (500-1)	720-1¾ 634 (700-1¾)	720-2 634 (700-2)

REIL Rwy 18   36 357° 6 NM from FAF

MIRL Rwy 18-36  from FAF

FAF to MAP 6 NM

Knots	60	90	120	150	180
Min:Sec	6:00	4:00	3:00	2:24	2:00

SC-4, 21 APR 2022 to 19 MAY 2022

SC-4, 21 APR 2022 to 19 MAY 2022