



RNAV (GPS) PRM RWY 8R
(SIMULTANEOUS CLOSE PARALLEL)
 HARTSFIELD-JACKSON ATLANTA INTL (ATL)


WAAS CH 48800 W08D	APP CRS 095°	Rwy Idg TDZE 1024 Apt Elev 1026	9999
--	------------------------	---	-------------

RNP APCH.	For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C, or above 54°C. Simultaneous close parallel approach authorized with ILS PRM and RNAV PRM Rwy 9L or 9R or 10, or Rwys 9L and 10, or Rwys 9R and 10. See additional requirements on AAPP. Dual VHF comm required. Use of FD or AP providing RNAV track guidance required during simultaneous operations.	MISSED APPROACH: Climb to 1500 then climbing left turn to 3500 direct TROYS and hold.
-----------	--	---

D-ATIS ARR 119.65 DEP 125.55	ATLANTA APP CON 127.9 379.9	ATLANTA TOWER 8L-26R 8R-26L 9L-27R 9R-27L 10-28 RWYS 119.1 125.325 123.85 119.3 119.5 254.4 PRM 126.9	ALL RWYS (8L-26R, 8R-26L) (9L-27R, 9R-27L) 10-28 121.9 121.75 121.65 254.4	GND CON 121.9 121.75 121.65 254.4
--	---------------------------------------	--	---	---



CLNC DEL	118.1	CPDLC
----------	--------------	-------



SE-4, 16 JUN 2022 to 14 JUL 2022

SE-4, 16 JUN 2022 to 14 JUL 2022

RADAR REQUIRED

VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 67).				
GPEAT	PEARI	NZBIT	HARSN	RW08R
5000	5000	4000	2800	
GP 3.00° TCH 53				
1500 3500 TROYS ↑ ↙ △				
7.4 NM 3.5 NM 4.7 NM 5.4 NM				
CATEGORY	A	B	C	D
LPV DA		1282/40	258 (300-¾)	
LNAV/VNAV DA		1516-1⅓	492 (500-1⅓)	

