

RADAR MINS

22139

N1

RADAR INSTRUMENT APPROACH MINIMUMS

FORT SMITH, AR

Amdt 8F, 19MAY22 (22139) (FAA)

ELEV 469

FORT SMITH RGNL (FSM)

RADAR-1 120.9 343.75 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	26		AB	1040/24	594	(600-½)	CDE	1040-1¼	594	(600-1¼)
	2		AB	1140-1	691	(700-1)	CDE	1140-2	691	(700-2)
	8		AB	1200-¾	731	(800-¾)	CDE	1200-1½	731	(800-1½)
Ⓢ CIRCLING ALL RWY			AB	1200-1	731	(800-1)	C	1400-2¾	931	(1000-2¾)
			DE	1400-3	931	(1000-3)				

Circling CAT E NA when R-2401B active.

Circling NA for Cat E north of Rwy 8 and west of Rwy 20.

For inop ALS, increase S-8 CAT A and B visibility to 1 SM, CAT E visibility to 2 SM, and S-26 CAT E visibility to 1¾ SM.

Rwy 2 helicopter visibility reduction below ¾ SM NA.

Rwy 8 helicopter visibility reduction below ¾ SM NA.

Circling NA at night to Rwy 20 and 26.

HENRY POST AAF (KFSI), OK (Fort Sill) (Amdt 13, 19171 USA)

ELEV 1188

RADAR - (E) 120.55 322.4 **▽ ▲** NA

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATh/ HAA</u>	<u>CEIL-VIS</u>
ASR	36 ²		AB	1600/40	413	(500-¾)
			CDE	1600/50	413	(500-1)
	18		AB	1880-1	692	(700-1)
			CDE	1880-2	692	(700-2)
CIR ¹	18-36		AB	1880-1	692	(700-1)
			C	1880-2	692	(700-2)
			D	1920-2¼	732	(800-2¼)
			E	1940-2¾	752	(800-2¾)

When local altimeter setting not received, use Lawton-Ft Sill Rgnl altimeter setting.

¹Circling NA for CAT E W of Rwy 18-36.

²When ALS inop, increase CAT CDE RVR to 60.

16 JUN 2022 to 14 JUL 2022

16 JUN 2022 to 14 JUL 2022

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

22139

N1

SC-1

RADAR MINS

22139

N2

RADAR INSTRUMENT APPROACH MINIMUMS

LAWTON, OK

Amdt 4A, 10JAN00 (00010) (FAA)

ELEV 1110

LAWTON-FORT SILL RGNL (LAW)

RADAR-1 - 120.55 322.4

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	35		ABC	1560-¾	471	(500-¾)	D	1560-1	471	(500-1)
CIRCLING	ALL RWY		AB D	1600-1 1680-2	490 570	(500-1) (600-2)	C	1620-1½	510	(600-1½)

LAWTON, OK

Amdt 1B, 08AUG02 (02220) (FAA)

ELEV 1110

LAWTON-FORT SILL RGNL (LAW)

RADAR-2 - 120.55 322.4

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VS</u>
ASR	17		AB	1620-1	510	(600-1)	CD	1620-1½	510	(600-1½)
CIRCLING	ALL RWY		AB D	1620-1 1680-2	510 570	(600-1) (600-2)	C	1620-1½	510	(600-1½)

OKLAHOMA CITY, OK

Amdt 2A, 07APR11 (11153) (FAA)

ELEV 1299

WILEY POST (PWA)

RADAR-1 124.6 266.8 ▼

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	35R		AB D	1840-1 1840-1¾	541 541	(600-1) (600-1¾)	C	1840-1½	541	(600-1½)
CIRCLING	ALL RWY		AB D	1840-1 1880-2	541 581	(600-1) (600-2)	C	1840-1½	541	(600-1½)

16 JUN 2022 to 14 JUL 2022

16 JUN 2022 to 14 JUL 2022

SC-1

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

22139

N2

RADAR INSTRUMENT APPROACH MINIMUMS

**OKLAHOMA CITY, OK
WILL ROGERS WORLD (OKC)**

Amdt 21A, 13OCT16 (20030) (FAA)

ELEV 1296

RADAR-1 124.6 266.8 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	17L		ABCDE	1680/40	393	(400-¾)
	35R		ABCDE	1680/40	386	(400-¾)
	17R		ABCDE	1680/40	398	(400-¾)
	35L		ABCDE	1680/40	404	(400-¾)
CIRCLING	ALL RWY		A	1740-1¼	444	(500-1¼)
			B	1760-1¼	464	(500-1¼)
			C	1960-1¼	664	(700-1¼)
			D	2000-2¼	704	(800-2¼)
			E	2240-3	944	(1000-3)

For inoperative MALSR, increase S-17L, S-17R, and S-35L CAT E visibility to 1¼.

For inoperative ALSF, increase S-35R CAT E visibility to 1¼.

16 JUN 2022 to 14 JUL 2022


16 JUN 2022 to 14 JUL 2022

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

TINKER AFB (KTIK), (Oklahoma City) OK (20086 USAF)

ELEV 1291

RADAR - Ctc OKLAHOMA CITY APP CON (E) 118.95 323.1 

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
ASR	36 ¹		A	1940/24	649	(700-½)
			B	1940/40	649	(700-¾)
			C	1940/60	649	(700-1¼)
			D	1940-1½	649	(700-1½)
			E	1940-1¾	649	(700-1¾)
	18 ²		A	2000/40	733	(800-¾)
			B	2000/50	733	(800-1)
			C	2000-1¾	733	(800-1¾)
			D	2000-2	733	(800-2)
			E	2000-2¼	733	(800-2¼)
CIR ³	36		A	1940-1	649	(700-1)
			B	1940-1¼	649	(700-1¼)
			C	1940-1¾	649	(700-1¾)
			D	1980-2¼	689	(700-2¼)
			E	2040-2¾	749	(800-2¾)
	18		A	2000-1	709	(800-1)
			B	2000-1¼	709	(800-1¼)
			C	2000-2	709	(800-2)
			D	2000-2¼	709	(800-2¼)
			E	2040-2¾	749	(800-2¾)

¹When ALS inop, increase CAT A RVR to 50 and vis to 1 mile, CAT B RVR to 60 and vis to 1¼ miles, CAT C vis to 1¾ miles, CAT D vis to 2 miles, CAT E vis to 2¼ miles.

²When ALS inop, increase CAT A RVR to 50 and vis to 1 mile, CAT B RVR to 60 and vis to 1¼ miles, CAT C vis to 2 miles, CAT D vis to 2¼ miles, CAT E vis to 2½ miles.

³CAT E circling not authorized in sector S of Rwy 13-31 and W of Rwy 18-36.

16 JUN 2022 to 14 JUL 2022

16 JUN 2022 to 14 JUL 2022

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

TULSA, OK

Amdt 19, 19MAY22 (22139) (FAA)

ELEV 678

TULSA INTL (TUL)

RADAR-1 124.0 338.3 **▽ ▲**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	18L		AB	1040/24	399	(400-½)	CDE	1040/35	399	(400-¾)
	18R		ABCD	1040-1	372	(400-1)	E	NA		
	26		ABCDE	1080-¾	428	(500-¾)				
	8		AB	1080-1	409	(500-1)	CDE	1080-1½	409	(500-1½)
	36R		AB	1120/24	470	(500-½)	CDE	1120/50	470	(500-1)
	36L		AB	1180-1	502	(600-1)	CD	1180-1½	502	(600-1¾)
			E	NA						
ⓐ	CIRCLING	ALL RWY	AB	1180-1	502	(600-1)	C	1500-2½	822	(900-2½)
			D	1520-2¾	842	(900-2¾)	E	1520-3	842	(900-3)

Circling NA for CAT E south of Rwy 8-26.

For inop ALS increase ASR S-18L CAT E visibility to RVR 6000.

For inop ALS increase ASR S-26 CAT A/B visibility to 1 SM, and CAT E visibility to 1¼ SM.

For inop ALS increase ASR S-36R CAT C/D/E visibility to 1¾ SM.

16 JUN 2022 to 14 JUL 2022

16 JUN 2022 to 14 JUL 2022

RADAR INSTRUMENT APPROACH MINIMUMS