FAIRFIELD, CALIFORNIA

# RNAV (GPS) RWY 03R

| WAAS CH 98057 W03B | APCH CRS 035° | Rwy ldg 10,995<br>TDZE 59<br>Arpt Elev 63 |
|---|---|---|

AL-488 (USAF)

TRAVIS AFB (KSUU)

* Circling NA NW of RWY 3L-21R.

MISSED APPROACH: Climb to 4500 direct FOLNO, track 308° to SEATO and hold, continue climb-in-hold to 4500.

| ATIS | APP CON | TOWER | GND CON | CLNC DEL |
|---|---|---|---|---|
| 135.55 292.125 | 119.9 322.325 (S)<br>126.6 281.45 (N) | 120.75 254.4 | 121.8 289.4 | 127.55 335.8 |

RNP APCH

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.

Radar required when holding above 6000.

5 NM 343° 163° SEATO

2783

FOLNO 199

RW03R

WUSMO 035° 253 427

1900 (3) (FAF) LUDEC 306

2500 036° (6.5) HEIDY 1159

(IF/IAF) HABAL

MSA RW03R 25 NM 5100

EMERG SAFE ALT 100 NM 12,600

4500 FOLNO tr 308° SEATO

ELEV 63 TDZE 59

HABAL 3000 036° HEIDY 2500 LUDEC 1900 035° WUSMO 900 1.3 NM to RW03R RW03R

GP 3.00° TCH 50

VGSI and RNAV glidepath not coincident (VGSI angle 2.50°/TCH 69)

3.1 NM 2.5 NM

TWR 209 3R 21L 3L 11,001 x 300 10,995 x 150 3500 x 80 032° 212° ASSAULT STRIP

035° to RW03R

| CATEGORY | A | B | C | D | E |
|---|---|---|---|---|---|
| LPV DA | 259/40 | | 200 | (200-¾) | |
| LNAV/VNAV DA | 340/45 281 (300-⅞) | 351/45 292 (300-⅞) | 359/45 300 (300-⅞) | 370/45 311 (400-⅞) | |
| LNAV MDA | 460/55 401 (400-1) | | 460/60 401 (400-1⅛) | | |
| C CIRCLING* | 560-1 497 (500-1) | 660-1 597 (600-1) | 1100-3 1037 (1100-3) | 1200-3 1137 (1200-3) | |

TDZL/CL Rwys 3R, 21L
MIRL Rwy 032°-212°
HIRL Rwys 3L-21R, 3R-21L

FAIRFIELD, CALIFORNIA

38°16'N - 121°55'W

TRAVIS AFB (KSUU)

Orig 27JAN22
TERPS

RNAV (GPS) RWY 03R



SW-2, 01 DEC 2022 to 29 DEC 2022