

TEXOMA FOUR DEPARTURE

ATIS 120.7
 CLNC DEL
 124.65
 GND CON 121.9
 MEACHAM TOWER
 118.3 257.8
 REGIONAL DEP CON
 118.1 306.95 (NORTH)
 135.975 379.9 (SOUTH)

**TOP ALTITUDE:
 ASSIGNED BY ATC**

TULSA
 114.4 TUL :...
 Chan 91
 N36°11.78'-W95°47.29'
 L-15, H-6

RADAR and DME required.

WILL ROGERS
 114.1 IRW :...
 Chan 88
 N35°21.52'-W97°36.55'
 L-15, H-6

OKMULGEE
 114.9 OKM :...
 Chan 96
 N35°41.58'-W95°51.96'
 L-15, H-6

ROLLS
 N35°43.36'
 W99°28.24'
 L-15, H-6

DECKK
 N34°52.37'
 W97°16.87'
 L-17, H-6

NOOGY
 N34°25.65'
 W96°59.06'

ZEMMA
 N34°23.03'
 W96°59.40'
 L-17, H-6

EAKER
 N34°19.05'
 W96°37.19'
 L-17, H-6

ARDMORE
 116.7 ADM :...
 Chan 114
 N34°12.70'-W97°10.09'
 L-17, H-6

BLECO
 N33°27.05'
 W97°06.54'
 L-17

GRABE
 N33°27.09'
 W96°57.69'
 L-17

BONHAM
 114.6 BYP :...
 Chan 93

RANGER
 115.7 FUZ :...
 Chan 104
 N32°53.37'-W97°10.77'

TAKEOFF MINIMUMS

Rwys 16, 17: Standard.
 Rwy 34: 300-2 or standard with minimum climb of 225' per NM to 1100, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 2000' prior to DER.
 Rwy 35: 300-1½ or standard with minimum climb of 210' per NM to 900, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 1200' prior to DER.

(NARRATIVE ON FOLLOWING PAGE)

(NOTES CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

TEXOMA FOUR DEPARTURE

SC-2, 23 MAR 2023 to 20 APR 2023

SC-2, 23 MAR 2023 to 20 APR 2023