

INDY ONE DEPARTURE

AL-203 (FAA)

INDIANAPOLIS INTL (IND)
INDIANAPOLIS, INDIANA

D-ATIS 134.25
CLNC DEL
128.75 257.8
CPDLC
GND CON
121.9
INDY TOWER
120.9 257.8
INDIANAPOLIS DEP CON
124.95 317.8 (EAST)
119.05 317.8 (WEST)

RADAR required.

BOILER
115.1 BVT
Chan 98
N40°33.37'-W87°04.16'
L-27, H-5

MARION
108.6 MZZ
Chan 23
N40°29.60'-W85°40.76'
L-27, H-5-10

TOP ALTITUDE:
(JETS) 5000
(PROPS) 3000

ROSEWOOD
117.5 ROD
Chan 122
N40°17.27'-W84°02.59'
L-27, H-10

CHAMPAIGN
110.0 CMI
Chan 37
N40°02.07'-W88°16.56'
L-27

LOCALIZER
111.75 I-UZK
Chan 54(Y)


I-OQV
0.3
050°
070°

BRICKYARD
116.3 VHP
Chan 110
N39°48.88'-W86°22.05'
L-27, H-5-10

LOCALIZER
111.15 I-OQV
Chan 48(Y)

DAYTON
114.5 DGN
Chan 92
N40°00.99'-W84°23.81'
L-27, H-10

TERRE HAUTE
115.3 TTH
Chan 100
N39°29.34'-W87°14.94'
L-27, H-5



LOCALIZER
111.15 I-FVJ
Chan 48(Y)

R-3401B

R-3401A

SHELBYVILLE
116.15 SHB
Chan 108 (Y)
N39°37.95'-W85°49.46'
L-27, H-5-10

HOOSIER
110.2 OOM
Chan 39
N39°08.63'-W86°36.78'
L-27

R-3403B

CINCINNATI
117.3 CVG
Chan 120
N39°00.96'-W84°42.20'
L-26-27

R-3403A

POCKET CITY
113.3 PXV
Chan 80
N37°55.70'-W87°45.74'
L-16, H-5

TAKEOFF MINIMUMS:

Rwy 5L/R, 14, 23L/R, 32: Standard.

NOTE: Select appropriate localizer/DME frequency/channel prior to departure.
NOTE: Jet aircraft accelerate to 250K until reaching 10000. If unable advise ATC.

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.