


APP CRS	Rwy Idg	<b>10553</b>
<b>123°</b>	TDZE	<b>540</b>
	Apt Elev	<b>618</b>


# RNAV (RNP) Z RWY 12R

ST LOUIS LAMBERT INTL (STL)

**V** For uncompensated Baro-VNAV systems, procedure NA below -16°C (4°F) or above 54°C (130°F). GPS required. For inop ALS, increase RNP 0.30 all Cats visibility to 1½ SM. Simultaneous approach authorized with Rwy 11 except for arrivals at RRRIP and HRBEE. Use of FD or AR required during simultaneous operations.

**MALSR**  
  
**MISSED APPROACH:** Climb to 5000 on track 123° to FONTI and hold, continue climb-in-hold to 5000.

D-ATIS <b>125.025</b> <b>379.925</b>	ST. LOUIS APP CON <b>132.125 360.6</b>	ST. LOUIS TOWER <b>118.5 257.7</b>	GND CON <b>121.9 348.6</b> (Inbound) <b>121.65 377.175</b> (Outbound) <b>118.925 227.125</b> (Rwy 11/29)	CLNC DEL <b>119.5 363.1</b>	CPDLC
--	---	---------------------------------------	---	--------------------------------	-------




NC-3, 23 MAR 2023 to 20 APR 2023

NC-3, 23 MAR 2023 to 20 APR 2023

ELEV 618	<b>D</b> TDZE 540
----------	-------------------

Rwy 6-24 7603 X 150  
 Rwy 11-29 9000 X 150  
 Rwy 12L-30R 9013 X 150  
 Rwy 12R-30L 11020 X 200



GP 3.00°	TCH 54
CATEGORY	A B C D
RNP 0.30 DA	998/60 458 (400-1¼)

HIRL all Rwys  
 TDZ/CL Rwys 11, 12L, 12R, 29, and 30R

## AUTHORIZATION REQUIRED