LOC I-SCH	APP CRS	Rwy Idg	7001
109.7	040°	TDZE	338
		Apt Elev	378

ILS or LOC RWY 4

SCHENECTADY COUNTY (SCH)

T ANA Circling Rwy 10 NA at night. Inop table does not apply to S-ILS 4. For inop MALSR, increase S-LOC 4 Cat A/B visibility to 1 mile and Cat C/D visibility to 1⅜ mile. For inoperative MALSR when using Albany altimeter setting, increase S-LOC 4 Cat A/B visibility to 1mile. When using Albany altimeter setting inoperative table does not apply to S-ILS-4. ADF required. When local altimeter setting not received, use Albany altimeter setting and increase all DA 33 feet, and all MDA 40 feet. Helicopter visibility reduction below ¾ SM NA.

MALSR

MISSED APPROACH: Climb to 1500 on 040° course and on HEU NDB bearing 045° then climbing right turn to 3700 direct HEU NDB and hold, continue climb-in-hold to 3700.

AWOS-3	ALBANY APP CON	SCHENECTADY TOWER ★	GND CON	UNICOM
119.275	132.825 263.075	121.3 (CTAF) L 321.1	121.9	122.95

ALTERNATE MISSED APCH FIX

ALBANY ALB 115.3 Chan 100

R-283 103° 283°

HUNTER 356 HEU

HEU 225°

820 045° 505± 742

LOCALIZER 109.7 I-SCH

1449 HEU 038°

1659 688± 1687

982 (IAF) HANLY OM/INT

R-293 3600 293° (8.1)

1122 040° R-273

(CFBMK) BUMPS INT

265° 085°

ALBANY 115.3 ALB Chan 100

MSA HEU 25 NM 3700

2294 1934 220°

ELEV 378 TDZE 338

REIL Rwy 28

HIRL Rwy 4-22 L

MIRL Rwy 10-28 L

TWR 389

7001 X 150

0.9% UP

4850 X 150

10 22 28 A5

040° 5.1 NM from FAF

Remain within 10 NM

220° BUMPS INT 3600 3100 040° 2010 *2000

GS 3.00° TCH 55 3100

3.5 NM 5.1 NM

HANLY OM/INT 1500 040° crs HEU 045° 3700 HEU

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 51).

* LOC only.

CATEGORY	A	B	C	D
S-ILS 4		538-¾	200 (200-¾)	
S-LOC 4	820-¾	482 (500-¾)	820-1	482 (500-1)
CIRCLING	880-1	940-1	1120-2¼	1320-3
	502 (600-1)	562 (600-1)	742 (800-2¼)	942 (1000-3)

FAF to MAP 5.1 NM

Knots	60	90	120	150	180
Min:Sec	5:06	3:24	2:33	2:02	1:42

NE-2, 23 MAR 2023 to 20 APR 2023
NE-2, 23 MAR 2023 to 20 APR 2023