ILS or LOC RWY 28L

PITTSBURGH INTL (PIT)

LOC I-PFS	APP CRS		28L	28C
108.9	281°	Rwy ldg	11500	9708
		TDZE	1125	1134
		Apt Elev	1203	1203

Simultaneous approach authorized. For inop ALS, increase S-ILS 28L Cat E visibility to RVR 4000 and S-LOC 28L Cats C, D, E visibility to 1⅝ SM. DME from MMJ DME. Simultaneous reception of I-PFS and MMJ DME required.

MALSR

MISSED APPROACH: Climb to 4000 on heading 280° and HLG VOR/DME R-043 to HLG VOR/DME and hold.

D-ATIS	PITTSBURGH APP CON	PITTSBURGH TOWER	GND CON	CLNC DEL
ARR 127.25	123.95 360.8	128.3 291.7	SOUTH 121.9 348.6	126.75 353.7
DEP 135.9			NORTH 127.8 348.6	

CPDLC

MSA AGC 25 NM
3100
270°
3800
360°

LOCALIZER 108.9
I-PFS

HALIN INT
MMJ 8.1
RADAR

(IF/IAF)
COSLU INT
MMJ 11.2
RADAR

PITTZ INT
MMJ 5
RADAR

R-028

2041
4000
(3)

R-040 AGC

1357

3000

101°
1 min
281°

281°
(3.2)

281°

101°

1513±

2049

MONTOUR
Chan 57
MMJ
(112.0)
1517

4000 NoPT
to COSLU
281° (3.1)

(IAF)
PEETE INT
MMJ 14.3
RADAR

R-359

R-014

4000 to COSLU
028°
(12.7)

RADAR required for procedure entry from PEETE.

114.25 HLG
R-043
Chan 89 (Y)

MISSED APCH FIX
WHEELING
HLG
114.25
Chan 89 (Y)
223°
R-043
043°

ALTERNATE MISSED APCH FIX
R-310
130°
310°
ALLEGHENY
AGC
110.0
Chan 37

ALLEGHENY
110.0 AGC
Chan 37

ELEV 1203

TDZE 28L 1125
TDZE 28C 1134

D



REIL Rwy 10C
HIRL all Rwys
TDZ/CL Rwys 10L, 10R, 28L, 28R, 28C, and 32

FAF to MAP 5.7 NM					
Knots	60	90	120	150	180
Min:Sec	5:42	3:48	2:51	2:17	1:54

4000	hdg 280°	HLG R-043	HLG

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 70).

One Minute Holding Pattern



CATEGORY	A	B	C	D	E
S-ILS 28L	1325/18 200 (200-½)				
S-LOC 28L	1700/24 575 (600-½)		1700-1¼ 575 (600-1¼)		
SIDESTEP 28C	1700-1 566 (600-1)		1700-1½ 566 (600-1½)	1700-2 566 (600-2)	
C CIRCLING	1700-1 497 (500-1)		1880-2 677 (700-2)	1880-2¼ 677 (700-2¼)	1880-2½ 677 (700-2½)

NE-4, 23 MAR 2023 to 20 APR 2023