

WAAS CH <b>40315</b> <b>W27A</b>	APP CRS <b>274°</b>	Rwy Idg <b>5502</b> TDZE <b>134</b> Apt Elev <b>141</b>
----------------------------------------	------------------------	---------------------------------------------------------------

# RNAV (GPS) RWY 27


DECATUR COUNTY INDUSTRIAL AIR PARK (BGE)

**⚠** Baro-VNAV NA when using Tallahassee Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. VDP NA when using Tallahassee Intl altimeter setting. When local altimeter setting not received, use Tallahassee Intl altimeter setting and increase LPV DA to 429 feet and LNAV/VNAV DA to 651 feet; increase all MDAs 100 feet and increase LNAV/VNAV all Cats visibility ½ SM, LNAV Cat C visibility ¼ SM and Circling Cat C, D visibility ½ SM. For inoperative MALSR increase LNAV Cat D visibility to 1¼ mile. For inoperative MALSR, when using Tallahassee Intl altimeter setting increase LPV all Cats visibility to 1 mile.



**MALSR**

**MISSED APPROACH:**  
Climb to 2500 direct FLSI and hold.

AWOS-3PT <b>121.125</b>	TALLAHASSEE APP CON★ <b>128.7 254.3</b>	UNICOM <b>122.975</b> (CTAF)
----------------------------	--------------------------------------------	---------------------------------



ELEV 141	TDZE 134
----------	----------



CATEGORY	A	B	C	D
LPV DA	334-½		200 (200-½)	
LNAV/VNAV DA	556-1		422 (500-1)	
LNAV MDA	540-½	406 (400-½)	540-¾ 406 (400-¾)	540-1 406 (400-1)
CIRCLING	600-1	459 (500-1)	800-1¾ 659 (700-1¾)	860-2¼ 719 (800-2¼)

SE-4, 23 MAR 2023 to 20 APR 2023

SE-4, 23 MAR 2023 to 20 APR 2023