


APP CRS 353°	Rwy Idg 12000 TDZE 5354 Apt Elev 5434
------------------------	--


RNAV (RNP) Z RWY 34R

DENVER INTL (DEN)



▼ For uncompensated Baro-VNAV systems, procedure NA below -25°C (-13°F) or above 46°C (114°F). GPS required. For inoperative ALSF, increase RNP 0.10 all Cats visibility to RVR 6000 and RNP 0.20 all Cats visibility to 1½ mile and RNP 0.30 all Cats visibility to 2¼ mile. Simultaneous approach authorized. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ALSF-2

 MISSED APPROACH:
 Climb to 6000 then climbing left turn to 10000 direct HYGEN and hold.

D-ATIS ARR 125.6 379.9 DEP 134.025	DENVER APP CON 119.3 307.3 (NORTH) 120.35 379.3 (SOUTH)	DENVER TOWER 135.3 351.95	GND CON 121.35 379.175	CLNC DEL 118.75	CPDLC
--	---	-------------------------------------	----------------------------------	---------------------------	-------



RADAR REQUIRED



CATEGORY	A	B	C	D
RNP 0.10 DA		5739/40	385 (400-¾)	
RNP 0.20 DA		5849/60	495 (500-1¼)	
RNP 0.30 DA		5980-1½	626 (600-1½)	

AUTHORIZATION REQUIRED

SW-1, 22 FEB 2024 to 21 MAR 2024

SW-1, 22 FEB 2024 to 21 MAR 2024