RNAV (GPS) Y RWY 35R

WILL ROGERS WORLD (OKC)

WAAS	APP CRS	Rwy Idg	9802
CH 61218	356°	TDZE	1294
W35B		Apt Elev	1296

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C (11°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop ALSF, increase LPV and LNAV/VNAV Cat E visibility to RVR 4000. Increase LNAV all Cats visibility to RVR 5500. Simultaneous approach authorized with Rwy 35L. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ASR

ALSF-2

MISSED APPROACH: Climb to 5000 direct ATREC and hold, continue climb-in-hold to 5000.

D-ATIS	OKE CITY APP CON	ROGERS TOWER	GND CON	CLNC DEL
125.85	124.6 266.8	119.35 269.45	121.9 348.6	124.35







CATEGORY	A	B	C	D	E
LPV DA	1494/18 200 (200-½)				
LNAV/VNAV DA	1544/24 250 (300-½)				
LNAV MDA	1640/24 346 (400-½)		1640/40 346 (400-¾)		
C CIRCLING	1740-1 444 (500-1)	1760-1 464 (500-1)	1960-1¾ 664 (700-1¾)	2000-2¼ 704 (800-2¼)	2240-3 944 (1000-3)

SC-1, 11 JUL 2024 to 08 AUG 2024
SC-1, 11 JUL 2024 to 08 AUG 2024