ILS or LOC RWY 14

BOIRE FLD (ASH)

LOC I-ASH	APP CRS	Rwy Idg	5650
109.7	139°	TDZE	200
		Apt Elev	200

RADAR required for procedure entry.

For inop ALS, increase S-LOC Cat C/D visibility to 1¾ SM.

MALSR

MISSED APPROACH: Climb to 1000 then climbing left turn to 2000 on GDM VOR/DME R-082 to PELAN INT/GDM R-082/34.6 DME and hold.

ATIS	BOSTON APP CON	NASHUA TOWER ★	GND CON	CLNC DEL
125.1	124.9 269.075	133.2 (CTAF) L	121.8	121.8





CATEGORY	A	B	C	D
S-ILS 14	400-½ 200 (200-½)			
S-LOC 14	820-½ 620 (700-½)		820-1⅜ 620 (700-1⅜)	
C CIRCLING	840-1 640 (700-1)	860-1 660 (700-1)	920-2 720 (800-2)	980-2½ 780 (800-2½)



HIRL Rwy 14-32 L

REIL Rwy 32 L

FAF to MAP 4.3 NM					
Knots	60	90	120	150	180
Min:Sec	4:18	2:52	2:09	1:43	1:26

NE-1, 17 APR 2025 to 15 MAY 2025
NE-1, 17 APR 2025 to 15 MAY 2025