

WAAS CH 61299 W28A	APP CRS 275°	Rwy Idg TDZE 998 Apt Elev 1026
--	------------------------	--

RNAV (GPS) Y RWY 28

HARTSFIELD/JACKSON ATLANTA INTL (ATL)

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C (20°F) or above 54°C (130°F). Simultaneous approach authorized with Rwy 26R or 26L or 27R, or Rwys 26R and 27R. DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ALSIF-2

MISSED APPROACH:

Climb to 1500 then climbing left turn to 3000 direct SCARR and hold.

D-ATIS	ATLANTA	ATLANTA TOWER					ALL	GND CON			ALL		
ARR	APP CON	8L-26R	8R-26L	9L-27R	9R-27L	10-28	RWYS	(8L-26R,8R-26L)	(9L-27R,9R-27L)	10-28	RWYS		
DEP	125.55	127.9	379.9	119.1	125.325	123.85	119.3	119.5	254.4	121.9	121.75	121.65	254.4

The chart displays the RNAV (GPS) Y RWY 28 approach. Key features include:

- Altitudes:** 1304, 1179, 1311, 1260, 1174, 2700 (5), 4000 (7.6), 1465, 3100.
- Navigation Aids:** RWY28, JUBBA, WONZR, PRMAN, TERII.
- Obstacles:** 1179, 1311, 1260, 1174, 2700 (5), 4000 (7.6).
- SCARR:** 180° turn, 4 NM distance.
- MSA:** 25 NM radius, 3100 MSL.
- CLNC DEL:** 118.1
- CPDLC:** (blank)

ELEV 1026 **D** TDZE 998

RADAR REQUIRED

<div>1500 3000 SCARR</div> <div>*LNAV only.</div>		<div>JUBBA 2700</div> <div>WONZR 4000</div> <div>PRMAN 4000</div>		
<div>RWY28</div> <div>*1.2 NM to RWY28</div>		<div>GP 3.00° TCH 57</div>		
<div>1.2 NM 4 NM 5 NM 7.6 NM</div>		<div>2700 4000 275°</div>		
CATEGORY	A	B	C	D
LPV DA	1198/18		200 (200-½)	
LNAV/VNAV DA	1250/24		252 (300-½)	
LNAV MDA	1440/24	442 (500-½)	1440/45	442 (500-¾)

The detailed chart shows the RNAV (GPS) Y RWY 28 approach with various altitudes and navigation aids. Key features include:

- Altitudes:** 1500, 3000, 1353, 1230, 1150, 1100, 1050, 1000, 950, 900, 850, 800, 750, 700, 650, 600, 550, 500, 450, 400, 350, 300, 250, 200, 150, 100, 50, 0.
- Navigation Aids:** RWY28, JUBBA, WONZR, PRMAN, TERII.
- Obstacles:** 1353, 1230, 1150, 1100, 1050, 1000, 950, 900, 850, 800, 750, 700, 650, 600, 550, 500, 450, 400, 350, 300, 250, 200, 150, 100, 50, 0.
- SCARR:** 180° turn, 4 NM distance.
- MSA:** 25 NM radius, 3100 MSL.
- CLNC DEL:** 118.1
- CPDLC:** (blank)

ATLANTA, GEORGIA
Amdt 4A 12OCT17

HARTSFIELD/JACKSON ATLANTA INTL (ATL)

33°38'N-84°26'W

RNAV (GPS) Y RWY 28