

RNAV (GPS) RWY 5L
BATTLE CREEK EXEC AT KELLOGG FLD (BTL)

V For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C.
A Circling to Rwy 5R, 23L and 31 NA at night. When local altimeter setting not received, use Grand Rapids altimeter setting and increase LPV DA to 1425 feet and all visibilities $\frac{3}{4}$ SM; increase LNAV/VNAV DA to 1361 feet and all visibilities $\frac{1}{4}$ SM; increase all MDAs 120 feet and LNAV visibility Cat C and D $\frac{3}{4}$ SM and Circling visibility Cat C and D $\frac{1}{2}$ SM. VDP and Baro-VNAV NA when using Grand Rapids altimeter setting. Rwy 5L helicopter visibility reduction below $\frac{3}{4}$ SM NA.

MISSED APPROACH:
Climb to 2500 direct
WIPIL and hold.

UNICOM
122.95

EC-1, 10 JUL 2025 to 07 AUG 2025

EC-1, 10 JUL 2025 to 07 AUG 2025

BATTLE CREEK EXEC AT KELLOGG FLD (BTL)
RNAV (GPS) RWY 5L

42°18'N-85°15'W