

LOC/DME I-BRO	APP CRS	Rwy Idg	7399
110.3	132°	TDZE	19
Chan 40		Apt Elev	22

ILS or LOC RWY 13

BROWNSVILLE/SOUTH PADRE ISLAND INTL (BRO)

ADF or RADAR required.

▼

VDP NA when using Port Isabel altimeter setting. For inop ALS increase S-LOC 13 Cats C and D visibility to 1 3⁄8 miles. When local altimeter setting not received, use Port Isabel altimeter setting and increase DA to 307 feet and all MDA 40 feet. S-LOC 13 Cat C and D visibility to RVR 5500, Circling Cat D visibility to 2 1⁄4 miles. For inop ALS when using Port Isabel altimeter setting increase S-LOC 13 Cats C/D visibility to 1 3⁄8 miles.

MALSR

AS

MISSED APPROACH:

Climb to 700 then climbing left turn to 2000 direct HRL VOR/DME and hold.

ATIS	VALLEY APP CON	BROWNSVILLE TOWER *	GND CON	UNICOM
128.55	119.5 257.6	118.9 (CTAF) 239.3	121.9	122.95

ELEV 22		D		TDZE 19					
<div>Remain within 10 NM</div> <div><div>DEPOO LOM I-BRO 7.3</div><div>700</div><div>2000</div><div>HRL</div></div> <div><div>1900</div><div>312°</div><div>1848</div><div>1900</div><div>132°</div><div>GS 2.75°</div><div>TCH 58</div></div> <div><div>4.6 NM</div><div>1.4 NM</div></div> <div><div>*I-BRO 2.8</div><div>I-BRO 1.4</div><div>*LOC only.</div></div>									
CATEGORY	A	B	C	D					
S-ILS 13	269/24		250 (300-1⁄2)						
S-LOC 13	480/24 461 (500-1⁄2)		480/50 461 (500-1)						
CIRCLING	480-1 458 (500-1)		540-1 518 (600-1)						
	540-1 518 (600-1)		540-1 518 (600-1 1⁄2)						
			680-2 658 (700-2)						
MIRL Rwy 18-36 HIRL Rwy 13-31									
FAF to MAP 6 NM									
Knots		60	90	120	150 180				
Min:Sec		6:00	4:00	3:00	2:24 2:00				

BROWNSVILLE, TEXAS

Orig-B 20JUN19

BROWNSVILLE/SOUTH PADRE ISLAND INTL (BRO)

25°54'N-97°26'W

ILS or LOC RWY 13