

WAAS CH 70307 W27A	APP CRS 265°	Rwy Idg TDZE Apt Elev	7985 6121 6160
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 27

CHEYENNE RGNL/JERRY OLSON FLD (CYS)

RNP APCH

▼

ASR/PAR

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -24°C or above 45°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4000.
RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

AS

MISSED APPROACH: Climb to 6600, then climbing right turn to 10400 direct SENSE and hold, continue climb-in-hold to 10400.

ATIS 134.425 278.3	CHEYENNE APP CON★ 124.55 263.075	CHEYENNE TOWER★ 118.7(CTAF) 0 257.8	GND CON 121.9 254.275	UNICOM 122.95
------------------------------	--	---	---------------------------------	-------------------------

MSA RW27 25 NM

10200

7 NM

270°

090°

SENSE

6513

CHEYENNE CYS

8500 to COLLA

101°

13

6584±

6239

6339

6302

265°

7800

266°

7.8

(FAF) HORSE

086°

6 NM

(IAF) EGBER

7800 NoPT

17°

7.2

(IAF) FERBU

8100

151°

51

VIDEE

8200

151°

51

POGTE

7800 NoPT

35°

8.3

(IAF) CRIMS

7800 NoPT

246°

11.4

COLLA

(IF/IAF)

7800

266°

7.8

6600

10400

SENSE

△

6 NM Holding Pattern

HORSE

COLLA

7800

266°

086°

7800

GP 3.00°

TCH 55

7.8 NM

3.9 NM

1.3 NM

RW27

265°

7800

266°

1.3 NM to RW27

* LNAV only

TWR 6256

9270 X 150

0.4° DOWN

0.7° UP

AS

265° to RW27

ELEV 6160

TDZE 6121

ELEV 6160

D

TDZE 6121

REIL Rwy 9, 13 and 31

HIRL Rwy 9-27

MIRL Rwy 13-31

AS

6256

9270 X 150

0.4° DOWN

0.7° UP

AS

265° to RW27

CATEGORY	A	B	C	D
LPV DA#	6321/24 200 (200-½)			
LNAV/VNAV DA	6376/24 255 (300-½)			
LNAV MDA	6560/24 439 (400-½)		6560/40 439 (400-¾)	
CIRCLING	6640-1 480 (500-1)		6900-2 740 (800-2)	6920-2½ 760 (800-2½)

CHEYENNE, WYOMING
Amdt 1A 28FEB19

CHEYENNE RGNL/JERRY OLSON FLD (CYS)

41°09'N-104°49'W

RNAV (GPS) RWY 27

NW-1, 10 JUL 2025 to 07 AUG 2025

NW-1, 10 JUL 2025 to 07 AUG 2025