

ILS or LOC RWY 5L

LOC I-FAE
109.7

APCH CRS
053°

Rwy Idg **12,600**
TDZE **803**
Arpt Elev **823**

[USAF]

WRIGHT-PATTERSON AFB (KFFO)

DME or RADAR required for Localizer.

ALSIF-1

↑ MISSED APPROACH: Climb to 2000 via FFO R-053 at 5 DME, turn right direct CLACK climbing to 3100 and hold.

ATIS
124.475 269.9

COLUMBUS APP CON
118.85 269.275

PATTERSON TOWER
127.8 281.45

GND CON
121.8 335.8

** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE vis to 1½ miles.

*** When Rwy 23R VGSi inop, circling to Rwy 23R NA at night.

ELEV 823

TDZE 803

CATEGORY	A	B	C	D	E
S-ILS 5L *	1003/24		200	(200-½)	
S-LOC 5L **	1280/24 476 (500-½)		1280/50 476 (500-1)		
CIRCLING ***	1380-1 557 (600-1)	1440-1 617 (700-1)	1560-2 737 (800-2)	1620-2½ 797 (800-2½)	1620-2¾ 797 (800-2¾)

DAYTON, OHIO
Amdt 4 28DEC23

39° 50'N-84° 03'W

WRIGHT-PATTERSON AFB (KFFO)

ILS or LOC RWY 5L

EC-2, 10 JUL 2025 to 07 AUG 2025

EC-2, 10 JUL 2025 to 07 AUG 2025