LOC I-PAE	APP CRS	Rwy Idg	9010
109.3	163°	TDZE	570
		Apt Elev	608

ILS Z RWY 16R (SA CAT II)

SEATTLE PAINE FLD INTL (PAE)

T DME required. Reduced Lighting: Requires specific OPSPEC, MSPEC, or LOA approval and use of autoland or HUD to touchdown. DME from PAE VOR/DME. Simultaneous reception of I-PAE and PAE DME required. Procedure NA when control tower closed.

MALSR

MISSED APPROACH: Climb to 1100 then climbing right turn to 3000 on heading 280° and PAE VOR/DME R-236 to ECEPO/PAE 9 DME and hold, continue climb-in-hold to 3000.

ATIS	SEATTLE APP CON	PAINE TOWER ★	GND CON	CLNC DEL	UNICOM
128.65	128.5 306.9	132.95 (CTAF) L 256.7	121.8 339.8	127.175	122.95



ELEV 608 D TDZE 570



TDZ/CL Rwy 16R
HIRL Rwy 16R-34L L
REIL Rwys 16L and 34R
MIRL Rwy 16L-34R



CATEGORY	A	B	C	D
S-ILS 16R	RA 116/12 100 DA 670			

SA CATEGORY II ILS-SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED

NW-1, 10 JUL 2025 to 07 AUG 2025
NW-1, 10 JUL 2025 to 07 AUG 2025