

WAAS

CH **53412**

**W34A**

APP CRS

**344°**

Rwy Idg

**7455**

TDZE

**680**

Apt Elev

**710**

**RNAV (GPS) RWY 34**

FORT WORTH MEACHAM INTL (FTW)

**⚠**

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C (23°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop MALS, increase LNAV/VNAV Cat D and LNAV Cat D visibility to 1½ mile.

MALS

MISSED APPROACH:

Climb to 3000 direct WOROD and hold.

ATIS <b>120.7</b>	LONE STAR APP CON (North) <b>118.1 306.95</b> (South) <b>135.975 379.9</b>	MEACHAM TOWER <b>118.3 257.8</b>	GND CON <b>121.9</b>	CLNC DEL <b>124.65</b>
----------------------	----------------------------------------------------------------------------------	-------------------------------------	-------------------------	---------------------------

MISSED APCH FIX

MSA RW34 25 NM

ELEV 710

**D**

TDZE 680

3000		WOROD		4 NM Holding Pattern	
*LNAV only		*1.3 NM to RW34		GP 3.00° TCH 60	
RW34		WAGMU 2.6 NM to RW34		DOJED	
1.3 NM		1.3 NM		2 NM	
1560*		2200		6 NM	
CATEGORY		A		B	
LPV DA		880-¾		200 (200-¾)	
LNAV/VNAV DA		1091-1½		411 (400-1½)	
LNAV MDA		1160-¾		1160-1½	
CIRCLING		1260-1		1280-1	
550 (600-1)		570 (600-1)		1340-1¾	
				630 (700-1¾)	
				1500-2½	
				790 (800-2½)	

FORT WORTH, TEXAS

Amdt 1 18SEP14

32°49'N-97°22'W

FORT WORTH MEACHAM INTL (FTW)

**RNAV (GPS) RWY 34**